


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 8 Township Number T 14 S Range Number R 8 E
 County: MORRIS
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: RA D Leea
 RR#, St. Address, Box #: Box 8
 City, State, ZIP Code: Dought, KS 66849
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 47 ft. ELEVATION:
 Depth(s) Groundwater Encountered: 47 ft. 2. 47 ft. 3. 47 ft.
 WELL'S STATIC WATER LEVEL: 47 ft. below land surface measured on 8/27/91
 Pump test data: Well water was 47 ft. after 47 hours pumping 47 gpm
 Est. Yield 47 gpm: Well water was 47 ft. after 47 hours pumping 47 gpm
 Bore Hole Diameter: 47 in. to 47 ft., and 47 in. to 47 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass ROCK Threaded X
 Blank casing diameter: 30 in. to 30 ft., Dia. 30 in. to 30 ft., Dia. 30 in. to 30 ft.
 Casing height above land surface: 42" Below in., weight 42" Below lbs./ft. Wall thickness or gauge No. 42" Below
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) N/A
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) N/A
 SCREEN-PERFORATED INTERVALS: From 4 ft. to 3 1/2 ft., From 4 ft. to 3 1/2 ft., From 4 ft. to 3 1/2 ft.
 GRAVEL PACK INTERVALS: From 4 ft. to 3 1/2 ft., From 4 ft. to 3 1/2 ft., From 4 ft. to 3 1/2 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 3 1/2 ft., From 4 ft. to 3 1/2 ft., From 4 ft. to 3 1/2 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Abandoned farmstead
 Direction from well? All How many feet? 20'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			<u>47</u>	<u>4</u>	<u>Subsoil</u>
			<u>4</u>	<u>3 1/2</u>	<u>BENTONITE</u>
			<u>3 1/2</u>	<u>0</u>	<u>SOIL</u>

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/27/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. LSV This Water Well Record was completed on (mo/day/yr) 9/9/91 under the business name of LSV by (signature) Nancy H. Rogers