

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: FRANKLIN		NW ¼ NE ¼ NW ¼	24	T 15 S	R 17 <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">E/W</span>
Distance and direction from nearest town or city street address of well if located within city? 6 3/4 west, 1 1/2 north of Centropolis					
2 WATER WELL OWNER: Tony Roberts					
RR#, St. Address, Box #: Rt. 1 Box 148			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: Overbrook, KS 66525			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 310' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 280' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 242' ft. below land surface measured on mo/day/yr 1-26-90			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 4 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8. 3/4 in. to ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic      3 Feedlot      6 Oil field water supply      9 Dewatering      12 Other (Specify below) 2 Irrigation      4 Industrial      7 Lawn and garden only      10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u> ...; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC		4 ABS	7 Fiberglass		Threaded
Blank casing diameter 5" in. to 0-260' ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 260 ft. to 310 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 310 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug					
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? west				How many feet? 128'	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Clay-Brown	237	265	Sandstone-Grey
6	22	Shale-Yellow	265	269	Limestone-Grey
22	24	Shale-Grey	269	302	Sandstone-Grey
24	31	Limestone-Grey	302-310		Shale-Grey
31	40	Shale-Grey			
40	59	Limestone-Grey			
59	64	Shale-Black			
64	65	Limestone-Grey			
65	70	Shale-Grey			
70	71	Limestone-Grey			
71	74	Shale-Grey			
74	85	Limestone-Grey			
85	122	Shale-Grey			
122	232	Sandy Shale-Grey			
232	237	Limestone-Grey			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-26-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 82. This Water Well Record was completed on (mo/day/yr) 1-9-90 under the business name of STRADER DRILLING CO., INC. by (signature) <i>Dee H. Strader</i>					