ILOCATION OF WATER WELL:   Fraction   SE & NW & NW & SE & NW & NW & SE & SE & SE & NW & NW & SE & S
Distance and direction from nearest town or city street address of well if located within city? 774 Stafford Road, Pomona KS  WATER WELL OWNER: Wood RR#, St. Address, Box # : 774 Stafford Road City, State, ZIP Code : Pomona KS  LOCATON WITH AN "X" IN Depth(s) Groundwater Encountered1 SECTION BOX: NA  Depth(s) Groundwater Encountered1 SECTION BOX: NA  SECTION BOX: NA  Depth(s) Groundwater Encountered1 NA  The below land surface measured on mo/day/yr Semple was submitted Section Section Medicing of the location of the Montoring value of the Section Medicing of the Montoring value of the Section Medicing of the Montoring value of the Section Medicing of the Montoring value of the Section No NA  Elevation: NA  Dature: NA  Dature: NA  Dature: NA  The below land surface measured on mo/day/yr Semple was submitted to Department? NA  The below land surface box in the Section No NA  Semple was submitted to Department? NA  Semple was submitted to Department? NA  Semple wa
Coated within city? 774 Stafford Road, Pomona KS   Latitude: NA   Longitude: NA   Longitude: NA   Longitude: NA   Data Collection Method: legal survey
Elevation: NA   Datum: Na
RR#, St. Address, Box # : 774 Stafford Road City, State, ZIP Code
SI LOCATE WELL'S  A DEPTH OF COMPLETED WELL 190 ft.  BOUTH AN "X" IN SECTION BOX:  WITH AN "X" IN SECTION BOX:  N
LOCATON WITH AN "X" IN SECTION BOX:    N
LOCATON WITH AN "X" IN SECTION BOX:  N WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gp Est. Yield gpm: Well water was ft. after hours pumping gp WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well 3 Sample was submitted Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr Sample was submitted Was a chemical/bacteriological sample submitted to Department? Yes No X TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 2 PVC 4 ABS 7 Fiberglass Alank casing diameter 3/4 in. to 190 ft., Dia in. to asing height below land surface 4 ft., Weight YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 8 Saw Cut 10 Other (specify) CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to From
WITH AN "X" IN SECTION BOX:  N WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gp Well WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Other (Specify below S Sample was submitted Water was ft. after hours pumping gp Well WATER TO BE USED AS: 5 Public water supply 9 Dewatering 2 Other (Specify below S Sample was submitted Water Well Disinfected? Yes No X TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 2 PVC 4 ABS 7 Fiberglass Polyethylene Threaded lank casing diameter 3/4 in. to 190 ft., Dia in. to ft., Dia in., to ft., Dia in., to ft., From ft. to ft., From ft., To
SECTION BOX:  N Pump test data: Well water was ft. after hours pumping gp Est. Yield gpm: Well water supply 8 Air conditioning 1 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Other (Specify below 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well 3 Estel 3 RMP (SR) 6 Asbestos-Cement 2 PVC 4 ABS 7 Fiberglass 1 Steel 3 RMP (SR) 6 Asbestos-Cement 2 PVC 4 ABS 7 Fiberglass 1 Steel 3 Stainless steel 5 Fiberglass 1 Steel 3 Stainless face 4 Stainless face 5 Storeglass face 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)  CREEN-PERFORATION OPENINGS ARE:  From ft. to ft.
Pump test data: Well water was ft. after hours pumping gp. Well water water supple gp. Detail water supply gp.
Est. Yield gpm: Well water was ft. after hours pumping gpm: Well water was ft. after hours pumping gpm: Well water was ft. after hours pumping gpm: Well water Steel of the Coll field water supply gpm. Well water supply gpm. Well water Steel of the Coll field water supply gpm. Well water Steel of the Coll field water supply gpm. Well water Steel of the Coll field water supply gpm. Well water well of the Coll field water supply gpm. Well water was garden gpm. Well water well of the Coll field water supply gpm. Well water was ft. after hours pumping gpm. Well water was ft. after hours pumping gpm. Well water supply gpm. Well water supply gpm. Well water was ft. after hours pumping gpm. Well water was ft. after hours pumping gpm. Well water supply gpm. Well water was ft. after hours pumping gpm. Well water supply gpm. Well water was hours well gpm. Well water was pumping gpm. Well water was power water supply gpm. Well water was pumping gpm. Well water water was pumping gpm. Well water
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 2 Other (Specify below 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well 2 Other (Specify below 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Geothermal Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr Sample was submitted Water Well Disinfected? Yes No X  TYPE OF CASING USED: 5 Wrought Iron 1 Steel 3 RMP (SR) 6 Asbestos-Cement 2 Other (specify below) Welded Fusion 2 PVC 4 ABS 7 Fiberglass Polyethylene Threaded lank casing diameter 3/4 in to 190 ft., Dia in to ft., Dia in to asing height below land surface 4 ft., Weight Ibs./ft. Wall thickness or gauge No. 160 PSI YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)  CREEN-PERFORATED INTERVALS: From ft. to ft. From ft.
Commercial   Domestic   3 Feed lot   6 Oil field water supply   9 Dewatering   10 Monitoring well   Cother (Specify below   Geothermal   10 Monitoring well   Geothermal   Geothermal   Steel   3 RMP (SR)   6 Asbestos-Cement   9 Other (specify below)   Welded   Fusion   1 Steel   3 RMP (SR)   6 Asbestos-Cement   9 Other (specify below)   Welded   Fusion   2 PVC   4 ABS   7 Fiberglass   Polyethylene   Threaded   lank casing diameter   3/4 in. to   190 ft., Dia   in. to   ft., Dia   in. to   saing height below land surface   4 ft., Weight   lbs./ft. Wall thickness or gauge No.   160 PSI   YPE OF SCREEN OR PERFORATION MATERIAL:   1 Steel   3 Stainless steel   5 Fiberglass   7 PVC   9 ABS   11 Other (specify)   2 Brass   4 Galvanized steel   6 Concrete tile   8 RM (SR)   10 Asbestos-Cement   12 None used (open hole)   CREEN OR PERFORATION OPENINGS ARE:   1 Continuous slot   3 Mill slot   5 Gauze wrapped   8 Saw Cut   10 Other (specify)   CREEN-PERFORATED INTERVALS: From   ft. to   ft. From   ft. to   ft. From   ft. to   From   ft. to   From   ft. to   ft. From   ft. to   From   ft. to   ft. Fr
SW   SE   Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr Sample was submitted
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr Sample was submitted Water Well Disinfected? Yes No X  TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Fusion  2 PVC 4 ABS 7 Fiberglass Polyethylene Threaded  lank casing diameter 3/4 in. to 190 ft., Dia in. to ft., Dia in. to sing height below land surface 4 ft., Weight lbs./ft. Wall thickness or gauge No. 160 PSI  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)  2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  From ft. to ft. From ft. to  GROUT MATERIAL: 1 Neat cement 2 Cement grout  3 Sentonite 4 Other  out Intervals From 4 ft. to 190 ft. From ft. to ft. From ft. to ft. From hat is the nearest source of possible contamination:  1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify)
TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 2 PVC 4 ABS 7 Fiberglass Polyethylene Threaded lank casing diameter 3/4 in. to 190 ft., Dia in. to ft., Dia in. to asing height below land surface 4 ft., Weight Ibs./ft. Wall thickness or gauge No. 160 PSI YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to GRAVEL PACK INTERVALS: From ft. to ft. From ft. to From ft. to ft. From ft. to GROUT MATERIAL: 1 Neat cement 2 Cement grout of the tild ft. From ft. to ft. From ft.
TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement Other (specify below) Welded Fusion  2 PVC 4 ABS 7 Fiberglass Polyethylene Threaded  lank casing diameter 3/4 in. to 190 ft., Dia in. to ft., Dia in. to saing height below land surface 4 ft., Weight lbs./ft. Wall thickness or gauge No. 160 PSI  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)  2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  Fout Intervals From 4 ft. to 190 ft. From ft. to ft. Fr
1 Steel 3 RMP (SR) 6 Asbestos-Cement 2 Polyethylene Threaded 2 PVC 4 ABS 7 Fiberglass Polyethylene Threaded 2 ank casing diameter 3/4 in. to 190 ft., Dia in. to ft., Dia in. to 2 sing height below land surface 4 ft., Weight Ibs./ft. Wall thickness or gauge No. 160 PSI 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) 3 CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) 3 CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to 4 GRAVEL PACK INTERVALS: From ft. to ft. From ft. to 5 From ft. to ft. From ft. to 6 GRAVEL PACK INTERVALS: From ft. to ft. From ft. to 7 From ft. to ft. From ft. to 8 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 9 Outlintervals From 4 ft. to 190 ft. From ft. to ft. From ft. The ft.
1 Steel 3 RMP (SR) 6 Asbestos-Cement 2 Polyethylene Threaded lank casing diameter 3/4 in. to 190 ft., Dia in. to ft., Dia in. to saing height below land surface 4 ft., Weight lbs./ft. Wall thickness or gauge No. 160 PSI YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other From ft. to ft. From ft. The ft. From ft. The ft. From ft. The ft. From ft. The ft. Th
Ising height below land surface 4 ft., weight loss./It. wall thickness or gauge No. 166 PSI YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)  2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  out Intervals From 4 ft. to 190 ft. From ft. to ft. From ft. The ft. From ft. to ft. From ft. The ft. From ft. The ft. The ft. The ft. From ft. The ft.
sing height below land surface 4 ft., weight loss./It. wall thickness or gauge No. 166 PSI YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)  2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  out Intervals From 4 ft. to 190 ft. From ft. to ft. From ft. The ft. From ft. to ft. From ft. The ft. The ft. From ft. The ft. The ft. The ft. From ft. The
A ft., weight below land surface 4 ft., weight loss./It. wall thickness or gauge No. 166 PSI SYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)  2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite  Out Intervals From 4 ft. to 190 ft. From ft. to ft. From ft. From ft. To ft. From ft. To ft. From ft. From ft. To ft. From ft. From ft. From ft. To ft. From
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  From ft. to ft. From ft. to  GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  cout Intervals From 4 ft. to 190 ft. From ft. to ft
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  From ft. to ft. From ft. to  GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite  From ft. to ft. From ft. ft. ft. From ft. ft. ft. From ft.
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  From ft. to ft. From ft. to  GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  Fout Intervals From 4 ft. to 190 ft. From ft. to ft. From ft. ft. From ft. to ft. From ft. ft. From ft. to ft. From ft. ft. ft. From ft.
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From ft. to ft. From ft. to  From ft. to ft. From ft. to  From ft. to ft. From ft. to  GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  rout Intervals From 4 ft. to 190 ft. From ft. to ft. From ft. ft. From ft. to ft. From ft. ft. From ft. to ft. From ft.
GRAVEL PACK INTERVALS: From ft. to ft. From ft
GRAVEL PACK INTERVALS: From ft. to ft. From ft
GRAVEL PACK INTERVALS: From ft. to ft. From ft
GRAVEL PACK INTERVALS: From ft. to ft. From ft. ft. From ft. ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. ft. ft. From ft. ft. ft. From ft. ft. From ft.
GROUT MATERIAL: 1 Neat cement 2 Cement grout (3) Bentonite 4 Other rout Intervals From 4 ft. to 190 ft. From ft. to ft. From ft. to ft. From ft. to ft. From 1 ft. From 1 ft. To ft. From 1 ft. To ft. From 1 ft. To ft. From 1 ft. From 1 ft. From 1 ft. From 1 ft. To ft. From 1 ft.
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other rout Intervals From 4 ft. to 190 ft. From ft. to ft. From ft. to ft. From ft. to ft. From 1 ft. ft. From 1 ft. to ft. From 1 ft. ft. ft. ft. ft. ft. From 1 ft.
tout Intervals From 4 ft. to 190 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. That is the nearest source of possible contamination:  1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specific pens)
hat is the nearest source of possible contamination:  1 Septic tank  4 Lateral lines 7 Pit privy  10 Livestock pens  13 Insecticide Storage  16 Other (specification)
2 Convey lines 5 Convey 1 9 Conveys leasen 11 Evel stances 14 Abandoned water well below
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well
rection from well? How many feet?
ROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 10 Top soil
10 20 Brown clay 20 30 Light gray shale 3-190 borings plugged
20 30 Light gray shale 3-190 borings plugged 30 90 Black red-dark gray shale
90 170 Light gray weathered shale 4 190 Bentonite
170 190 Weak sandstone
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS  0 10 Top soil 10 20 Brown clay 20 30 Light gray shale 30 90 Black red-dark gray shale 90 170 Light gray weathered shale 170 190 Weak sandstone  CONTRACTORS OR LANDOWNERS CERTIFICATION: This protocol was allowed as a contracted of Contracted as C
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugge
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugge der my jurisdiction and was completed on (mo/day/year) 10/1/12 and this record is true to the best of my knowledge and beli
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugge
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugge der my jurisdiction and was completed on (mo/day/year) 10/1/12 and this record it true to the best of my knowledge and belinsas Water Well Contractor's License No. 757 This Water Well Record was completed on conday/year) 10/8/12