

1	LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Franklin	NE ¼ NE ¼ SW ¼	30	T 15 S	R 19E E/W	

Distance and direction from nearest town or city street address of well if located within city? **franklin permit # 07-WW-FR-014**
1007 centropolis

2	WATER WELL OWNER:	G.L.M.C. Inc. C/O Gary Miller	west site
RR#, St. Address, Box # :	P.O. Box 831		Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Baldwin City, Ks. 66006		Application Number:

3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4	DEPTH OF COMPLETED WELL	ELEVATION:
		120		
Depth(s) Groundwater Encountered, 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on 1-14-07 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 12 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 <u>Domestic</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes X No		

5	TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 <u>PVC</u>	4 ABS	7 Fiberglass		Threaded
Blank casing diameter	5 in. to	ft., Dia	in. to	ft., Dia
Casing height above land surface	24 in., weight	2.82 lbs./ft.	Wall thickness or gauge No.	.258
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-Cement	
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	11 Other (Specify)
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Guazed wrapped	8 <u>Saw cut</u>	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS:	From 37 ft. to 47 ft.	From 100 ft. to 110 ft.		
GRAVEL PACK INTERVALS:	From 27 ft. to 120 ft.	From		

6	GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 <u>Bentonite</u>	4 Other
Grout Intervals:	From 3 ft. to 27 ft.	From	ft. to	ft. to	ft. to
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well	
2 <u>Sewer lines</u>	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	25	
Direction from well?	south	How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	22	brown clay			
22	30	clay brown sandy			
30	38	sandstone brown yellow			
38	46	sandstone grey			
46	49	limestone grey			
49	58	shale grey			
58	61	limestone grey			
61	63	shale grey			
63	70	sandstone grey			
70	72	sandstone grey shale			
72	73	shale black			
73	120	shale grey			

7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-14-07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 182 This Water Well Record was completed on (mo/day/yr) 1-17-08 under the business name of Strader Drilling Co., Inc. by (signature) <i>Jim Strader</i>
---	--