

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: <u>Douglas</u> Distance and direction from nearest town or city street address of well if located within city? <u>3 1/2 miles 1 1/2 south of Baldwin</u>		Fraction <u>NE 1/4 NE 1/4 SW 1/4</u> Section Number <u>14</u> Township Number <u>T 15 S</u> Range Number <u>R 19 W</u>		Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: _____ Longitude: _____ Elevation: _____ Datum: _____ Data Collection Method: _____																																											
2 WATER WELL OWNER: <u>Jessika Schoepplin</u> RR#, St. Address, Box # <u>57E 1250nd</u> City, State, ZIP Code <u>Baldwin City KS 66006</u>																																															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N <table border="1" style="margin: auto; border-collapse: collapse; text-align: center;"> <tr> <td style="padding: 5px;">-- NW --</td> <td style="padding: 5px;">-- NE --</td> </tr> <tr> <td style="padding: 5px;">W</td> <td style="padding: 5px;">E</td> </tr> <tr> <td style="padding: 5px;">-- SW --</td> <td style="padding: 5px;">-- SE --</td> </tr> <tr> <td colspan="2" style="padding: 5px;">S</td> </tr> </table>		-- NW --	-- NE --	W	E	-- SW --	-- SE --	S		4 DEPTH OF COMPLETED WELL <u>120</u> ft. Depth(s) Groundwater Encountered (1)... <u>29</u> ft. (2)..... ft. (3)..... ft. WELL'S STATIC WATER LEVEL... <u>25</u> ft. below land surface measured on mo/day/yr. <u>7-2-10</u> Pump test data: Well water was.....ft. after..... hours pumping..... gpm Est. Yield... <u>7</u> ...gpm: Well water was.....ft. after..... hours pumping..... gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well <u>1 Domestic</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>; If yes, mo/day/yr Sample was submitted..... Water well disinfected? Yes <u>Y</u> No																																					
-- NW --	-- NE --																																														
W	E																																														
-- SW --	-- SE --																																														
S																																															
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued... <u>Y</u> ... Clamped..... <u>1 Steel</u> 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded..... <u>2 PVC</u> 4 ABS 7 Fiberglass Threaded..... Blank casing diameter <u>5</u> in. to <u>8.35</u> ft., Diameter <u>8</u> in. to <u>10.5 to 30</u> ft., Diameter in. to ft. Casing height above land surface..... <u>24</u> in., Weight lbs./ft. Wall thickness or gauge No. <u>SDR 21</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass <u>7 PVC</u> <u>032</u> 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped <u>8 Saw Cut</u> 10 Other (specify) SCREEN-PERFORATED INTERVALS: From..... ft. to ft., From ft. to ft. From..... <u>35</u> ft. to <u>55</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From..... <u>3.1</u> ft. to <u>120</u> ft., From ft. to ft. From..... ft. to ft., From ft. to ft.																																															
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>3</u> ft. to <u>30</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank <u>4 Lateral line</u> 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well Direction from well? <u>SW</u> How many feet? <u>100 ft</u>																																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">FROM</th> <th style="width: 10%;">TO</th> <th style="width: 80%;">LITHOLOGIC LOG</th> </tr> </thead> <tbody> <tr><td>0</td><td>2</td><td>Topsoil</td></tr> <tr><td>2</td><td>14</td><td>Brown Clay</td></tr> <tr><td>14</td><td>22</td><td>Brown sandstone</td></tr> <tr><td>22</td><td>29</td><td>Gray shale</td></tr> <tr><td>29</td><td>46</td><td>Gray Sandstone</td></tr> <tr><td>46</td><td>51</td><td>Gray Limestone</td></tr> <tr><td>51</td><td>59</td><td>Gray shale</td></tr> <tr><td>59</td><td>61</td><td>Black shale</td></tr> <tr><td>61</td><td>82</td><td>Gray shale</td></tr> <tr><td>82</td><td>83</td><td>Gray limestone</td></tr> </tbody> </table>		FROM	TO	LITHOLOGIC LOG	0	2	Topsoil	2	14	Brown Clay	14	22	Brown sandstone	22	29	Gray shale	29	46	Gray Sandstone	46	51	Gray Limestone	51	59	Gray shale	59	61	Black shale	61	82	Gray shale	82	83	Gray limestone	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">FROM</th> <th style="width: 10%;">TO</th> <th style="width: 80%;">PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr><td>85</td><td>120</td><td>Gray shale</td></tr> <tr><td colspan="3" style="height: 100px; vertical-align: top;"> Note: Drilled 12" hole to 30", set 8" PVC 10-30 and grouted in </td></tr> </tbody> </table>				FROM	TO	PLUGGING INTERVALS	85	120	Gray shale	Note: Drilled 12" hole to 30", set 8" PVC 10-30 and grouted in		
FROM	TO	LITHOLOGIC LOG																																													
0	2	Topsoil																																													
2	14	Brown Clay																																													
14	22	Brown sandstone																																													
22	29	Gray shale																																													
29	46	Gray Sandstone																																													
46	51	Gray Limestone																																													
51	59	Gray shale																																													
59	61	Black shale																																													
61	82	Gray shale																																													
82	83	Gray limestone																																													
FROM	TO	PLUGGING INTERVALS																																													
85	120	Gray shale																																													
Note: Drilled 12" hole to 30", set 8" PVC 10-30 and grouted in																																															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ... <u>7-2-10</u> ... and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>182</u> ... This Water Well Record was completed on (mo/day/year) ... <u>7-13-10</u> ... under the business name of <u>Stade Drilling Co. Inc</u> by (signature) <u>[Signature]</u>																																															
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html .																																															