


1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 SW 1/4 Section Number 21 Township Number T 15 S Range Number R 2 E/W*
 County: Dickinson

Distance and direction from nearest town or city street address of well if located within city?
13 1/2 miles South of Abilene, Ks on Hwy 15 to 944 Hwy 15

2 WATER WELL OWNER: Don Reiff
 RR#, St. Address, Box # : 944 Hwy 15 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Hope, Kansas 67451 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 5.1 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 1.1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 9 ft. below land surface measured on mo/day/yr 7 / 1 / 0.6
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 1.0 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No *; If yes, mo/day/yrs sample was submitted
 Water Well Disinfected? Yes * No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued * Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 5.1 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 2.4 in., weight 2.00 lbs./ft. Wall thickness or gauge No. 2.50
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 1.1 ft. to 5.1 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 1.0 ft. to 5.1 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 1.0 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? EAST APPROX How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	DARK TOP SOIL			
6	1	ROCK			
1	3	DARK CLAY			
3	6	BROWN CLAY			
6	13	LITE COLOR SHALE & CLAY			
13	15	LIMESTONE & SHALE			
15	17	SOFT SHALE & CLAY			
17	28	DARK SHALE			
28	29	GRAY CLAY			
29	38	GRAY SHALE			
38	5.1	GRAY SHALE & GYPSUM			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7 / 1 / 0.6 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 39.7 This Water Well Record was completed on (mo/day/yr) 7 / 14 / 0.6 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold D. Martin