WATER WELL RECORD		Form W	WC-5	Di	vision of Wate	r Resources App. N	o. L			
1 LOCATION OF WATER WELL:		Fraction		Section		Township No.				
County: Franklin		1/4 NW 1/4 JL) ¼ NL) ½		21	T 15 S		\square W		
Street/Rural Address of Well Location; if unknown, distance & direction						System (GPS) in				
from nearest town or intersection: If at owner's address, check here \(\sumset\).					Latitude: (in decimal degrees)					
					Longitude: (in decimal degrees) Elevation:					
					Datum: WGS 84, NAD 83, NAD 27					
2 WATER WELL OWNER: Ed Mc Daniel				Collec	Collection Method:					
RR#, Street Address, Box #: 4819 Vermont Rd					GPS unit (Make/Model:)					
City, State, ZIP Code : We 11su, 11e, KS			Est. A	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m						
WITH AN "X" IN 4 D					ft.	2.18	10 DOLES			
SECTION BOX: Dep	Depin(s) Groundwater Encountered (1): M C				π. (2) π.					
WEI						below land surface measured on mo/day/yr				
1 1 ' 1 ' 1					ft. after hours pumpinggpm					
W Bore Hole Diameter					t., andin. toft.					
WELL WATER TO BE USED AS: ☐ Public water supply						othermal 🔲 I	njection well			
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Dewatering Other (Specify below								elow)		
Irrigation Industrial Domestic-lawn & garden Monitoring well C. A. S. C										
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted										
Water well disinfected? \[\sum \text{Yes} \sum \text{No} \]										
5 TYPE OF CASING USED: Steel PVC Other H.D. Poly. 8.thy. 18.n. 8										
CASING JOINTS: Glued Clamped Welded Threaded Fusion										
Casing diameter $3/4$ in to 180 ft Diameter in to ft Diameter in to ft										
Casing height about tand surface 36 in Weight SOKII lbs/ft Wall thickness or gauge No. 160 PST										
TYPE OF SCREEN OR PERFORATION MATERIAL: (N)										
Steel Stainless Steel PVC Unter (Specify)										
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: No Q										
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)										
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)										
SCREEN-PERFORATED INTERVALS: From										
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.										
From										
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other										
		3 ft., Fron	n	ft. to	ft.,	From	. ft. to	ft.		
What is the nearest source of po			□ T :41-		T		(:c -1-1)			
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						er (specify below))			
Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage					Oil well/ga					
Direction from well				from we	,					
	LITHOLOG	IC LOG	FROM	TO	LITHO. LO	OG (cont.) <u>or</u> PLU	GGING INTER	VALS		
	lay									
8 10 line										
10 18 Clay 18 79 Sand Stor							PW			
79 149 Shale	10		180	.3	5-180'	Bores Plugo	ed with			
149 /63 lime		100		High		tonite	<u> </u>			
163 172 Shale				J	<u> </u>	1.0				
172 180 line	172 180 line			····						
					~ ~					
7 CONTRACTORS OR I 13	AID O TEATRAIN	20 CEDTIEIO ATIO	N. This	on v 11				1		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 又 constructed, □ reconstructed, or □ plugged under my jurisdiction and was completed on (mo/day/year)										
Kansas Water Well Contractor's License No										
under the business name of EVAOS Energy Dev. Inc. by (signature)										
INSTRUCTIONS : Use typewriter or	ball point pen.	PLEASE PRESS FIRML	<u>Y</u> and <u>PRINT</u> cl	early. Ple	ase fill in blanks	and check the correc	t answers. Send thr	ree copies		
(white, blue, pink) to Kansas Departn Telephone 785-296-5522. Send one										
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.										
KSA 82a-1212										