WATE	R WEL	L RECORD	Form W	WC-5	Di	vision of Wate	r Resources App. No	0,	
1 LOCATION OF WATER WELL:			Fraction				Township No.	Range Number R	
		ddress of Well Location:	if unknown distance &	Globs	Clohal Positioning System (CPS) information:				
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here						Global Positioning System (GPS) information: Latitude:			
						Elevation:			
			DONAHOO		Colle	ction Method:			
		TD (2)	EADOW LANE		GPS unit (Make/Model:)				
			VILLE, KS 66092			Digital Map/Photo, Topographic Map, Land Survey Est. Accuracy: < 3 m, 3-5 m, 5-15 m, >15 m			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 200 ft. 3-200' BORES									
	TION BO	Depth(s) Groundwater Encountered (1)NONE ft. (2) ft. (3) ft.							
	N	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							
1 1	Pump test data: Well water wasft. after								
NV W	[NW]NC]								
"	WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well								
sw	Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well CLOSED LOOP Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No									
S If yes, mo/day/yr sample was submitted									
Water well disinfected? ☐ Yes ☑ No									
5 TYPE OF CASING USED: Steel PVC Other HD POLYETHYLENE									
CASING JOINTS: Glued Clamped Welded Threaded FUSION Casing diameter .3/4 in. to .200 ft., Diameter in. to ft., Diameter ft.									
Casing diameter 3/4									
TYPE OF SCREEN OR PERFORATION MATERIAL: NONE									
Steel Stainless Steel PVC Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: NONE									
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From									
SCREE	N-PERF	ORATED INTERVALS:						to ft. to ft.	
	GRAVI	EL PACK INTERVALS:							
			From	ft. to		ft., From	ft.	to ft.	
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other									
Grout Intervals: From 200 ft. to 3 ft., From ft. to ft., From ft., From ft., From ft. to ft., From ft.									
Septic tank									
Sewer lines Cesspool				ge	_				
□ Watertight sewer lines □ Seepage pit □ Feedyard □ Fertilizer storage □ Oil well/gas well □ Direction from well □ Distance from well									
FROM	TO	LITHOLOG		FROM	TO			IGGING INTERVALS	
0	22		SHALE						
22	35	SANDSTONE 160-180							
35	47		0 SHALE			<u> </u>			
47 74	74 79	LIME SHALE		200	3	3-200' BO	RES PLUGGED	WITH	
79	87	LIME		200			ID BENTONITE		
87	106	SANDSTONE							
106	114	LIME							
114	155	SHALE							
155 157 LIME									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\big \) constructed, \(\big \) reconstructed, or \(\big \) plugged under my jurisdiction and was completed on (mo/day/year) .04/28/20.15 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 561 This Water Well Record was completed on (mo/day/year) 94/29/2015									
under the business name of EVANS ENERGY DEVELOPMENT, INC. by (signature) INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to									
INSTRUC	CTIONS:	Use typewriter or ball point per	n. PLEASE PRESS FIRML)	and <u>PRINT</u>	dearly. Plo	ease fill in blanks Jackson St. Suit	s and check the correct e 420. Toneka Kansa	answers. Send one copy to as 66612-1367	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html									