LOCATION OF WATER WELL:   Fracion
Distance and direction from nearest town or city street address of well if located within city?    NATER WELL OWNER:   Sury Bus
WATER WELL OWNER: Stray Rice.  RR#, St. Address, Box #: 4142
WATER WELL OWNER:  RR#, St. Address, Box # : 44 12 o usedlorn Rd.  Dity, State, ZIP Code : Well Discountered   Code   Cod
R#, St. Address, Box # : 44 2 8 woollonk & Board of Agriculture, Division of Water Re Application Number:  LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL
Depth of Complete Well   1   1   1   1   1   1   1   1   1
DEPTH OF COMPLETED WELL.    The pump test data: Well water was   ft. after   hours pumping
Depth(s) Groundwater Encountered 1. 35 ft. 2 ft. 3 MeLL'S STATIC WATER LEVEL //7 ft. below land surface measured on mo/day/yr 3 2 3 9 S Pump test data: Well water was ft. after hours pumping Est. Yield / 0 gpm: Well water was ft. after hours pumping Bore Hole Diameter / in. to / 0 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well Domestic 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. A. If yes, mo/day/yr sample water well Disinfected? Yes A No  TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued A. Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVO 4 ABS 7 Fiberglass Threaded.  lank casing diameter in to 40 ft. Dia in to  PVC OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) Tontinuous slot 3 Mill slot 6 Wire wrapped 9 Dirilled holes
WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 3 - 23 - 9.5  Pump test data: Well water was ft. after hours pumping  Est. Yield 1.2 gpm: Well water was ft. after hours pumping  Bore Hole Diameter 2 in. to 1.2 ft., and in. to  WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  I Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 1.2 No.  TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 1.3 Clamped 1.5 Lank casing diameter 1.5 in. to 40 ft., Dia 1.5 in., Dia 1.
Pump test data: Well water was ft. after hours pumping st. Yield / 0. gpm: Well water was ft. after hours pumping st. Yield / 0. gpm: Well water was ft. after hours pumping st. Yield / 0. gpm: Well water was ft. after hours pumping st. Yield / 0. gpm: Well water was ft. after hours pumping st. Yield / 0. gpm: Well water was ft. after hours pumping st. Yield / 0. gpm: Well water supply 8 Air conditioning 11 Injection well water supply 9 Dewatering 12 Other (Specify below) 12 Injection well was a chemical/bacteriological sample submitted to Department? Yes. No. A. St. If yes, mo/day/yr sample water well Disinfected? Yes A No No. TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued A. Clamped 2 PVC 4 ABS 7 Fiberglass Threaded.  Stank casing diameter S in to 40 ft. Dia in to / 0 ft. Dia in
Est. Yield ./
Bore Hole Diameter & in. to
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well    Domestic   3 Feedlot   6 Oil field water supply 9 Dewatering 12 Other (Specify below)
TYPE OF BLANK CASING USED:  Steel 3 RMP (SR)  Stank casing diameter  Stank casing diameter  Stank casing height above land surface  1 Steel 3 Stainless steel 5 Fiberglass  2 Irrigation  1 I Domestic 2 Irrigation  4 Industrial 7 Lawn and garden only 10 Monitoring well  Water Well Disinfected? Yes \( \) No  Water Well Disinfected? Yes \( \) No  CASING JOINTS: Glued  CASING
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes
Was a chemical/bacteriological sample submitted to Department? Yes
TYPE OF BLANK CASING USED:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  2 PVC 4 ABS 7 Fiberglass Threaded.  3 In. to 40 ft., Dia in. to 10 ft., Dia in. to 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
TYPE OF BLANK CASING USED:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  2 PVC 4 ABS 7 Fiberglass Threaded.  In. to 40 ft., Dia in. to 100 ft., Dia in. to asing height above land surface.  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded.  Iank casing diameter 5 in to 40 ft., Dia 80 in to 100 ft., Dia in to asing height above land surface 7.8 in., weight Ibs./ft. Wall thickness or gauge No. 44 ABS  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
lank casing diameter in. to in. to ft., Dia in. to ft., Dia in. to in. weight above land surface ft. in., weight in., weight in., weight in. to in. in. to in. to in. to in. to in. to in. to
Assing height above land surface / § in., weight lbs./ft. Wall thickness or gauge No 10 Meight 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open here) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
CREEN-PERFORATED INTERVALS: From
From ft. to ft., From ft. to
GRAVEL PACK INTERVALS: From. 1.00 ft. to 2.0 ft., From ft. to
From ft. to ft., From ft. to
GROUT MATERIAL: 1 Neat cement 2 Cement grout 8 Bentonite 4 Other
From 3. ft. to 3.0 ft., From 5 ft. to 15 ft., From 15 ft. to 15
/hat is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water we
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
irection from well? South east How many feet? 166+
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
1 4 Tap soil.
4 8 Yellow clay,
8 13 rand stone.
13 35 Sandy Cay. watter at Boton.
35 100 Shale.
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction a
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction a simpleted on (mo/day/year) 3-23-95 and this record is true to the best of my knowledge and belief.
impleted on (mo/day/year)