

1 LOCATION OF WATER WELL: County: Johnson	Fraction SE 1/4 NW 1/4 NE 1/4	Section Number 13	Township Number T 15 S	Range Number R 24 E	
Distance and direction from nearest town or city street address of well if located within city? 20888 Benson Bucyrus, KS.					
2 WATER WELL OWNER: Tim Bowman		6-300 Bores			
RR#, St. Address, Box # : 20888 Benson		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Bucyrus KS. 66013		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 300 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 None ft. 2 None ft. 3 None ft.			
		WELL'S STATIC WATER LEVEL None ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was None ft. after None hours pumping None gpm			
		Est. Yield None gpm: Well water was None ft. after None hours pumping None gpm			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) H.D. Polyethylene Welded fusion Blank casing diameter 1 1/4 in. to 30.0 ft., Dia 40 in. to SDR 11 lbs./ft. Wall thickness or gauge No. 40 Casing height above land surface below in., weight 40 in., weight SDR 11 lbs./ft. Wall thickness or gauge No. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL: None					
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) None 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: None					
1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) None					
SCREEN-PERFORATED INTERVALS: From 300 ft. to 3 ft., From 300 ft. to 3 ft., From 300 ft. to 3 ft., From 300 ft. to 3 ft.					
GRAVEL PACK INTERVALS: From 300 ft. to 3 ft., From 300 ft. to 3 ft., From 300 ft. to 3 ft., From 300 ft. to 3 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 300 ft. to 3 ft., From 300 ft. to 3 ft., From 300 ft. to 3 ft., From 300 ft. to 3 ft.					
What is the nearest source of possible contamination: None					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? None How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	Soil & Clay	300	4	High solids bentonite
7	119	Limestone			
119	165	Shale			
165	179	Limestone			
179	202	Shale			
202	212	Limestone			
212	240	Shale			
240	265	Limestone			
265	273	Shale			
273	296	Limestone			
296	300	black shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **6-16-05** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No **561** This Water Well Record was completed on (mo/day/yr) **6-20-05** under the business name of **Evans Energy Dev. Inc.** by (signature) **Steve Evans**