

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Johnson		SW 1/4 SW 1/4 SE 1/4		6		T 15 S		R 25 E	
Distance and direction from nearest town or city street address of well if located within city? NA (MW-5)									
2 WATER WELL OWNER: PEMCO									
RR#, St. Address, Box #: 6450 S. Lewis									
City, State, ZIP Code: Tulsa, OK 74136									
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 9.5 ft. ELEVATION: 99.34'							
		Depth(s) Groundwater Encountered 1. 3.58 ft. 2. . ft. 3. . ft.							
		WELL'S STATIC WATER LEVEL 3.58 ft. below land surface measured on mo/day/yr 5/1/90							
		Pump test data: Well water was . ft. after . hours pumping . gpm							
		Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm							
		Bore Hole Diameter 7.25 in. to 9.5 ft., and . in. to . ft.							
		WELL WATER TO BE USED AS:							
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		7 Lawn and garden only ☒ 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes . No ☒ If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes ☒ No ☒							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped ☒ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass ☒ Threaded									
Blank casing diameter 4 in. to 4 ft., Dia . in. to . ft., Dia . in. to . ft.									
Casing height above land surface 0 in., weight . lbs./ft. Wall thickness or gauge No. Sch. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot ☒ 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 4 ft. to 9.5 ft., From . ft. to . ft.									
GRAVEL PACK INTERVALS: From 2.5 ft. to 9.5 ft., From . ft. to . ft.									
6 GROUT MATERIAL:									
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0.5 ft. to 2.5 ft., From 0.5 ft. to . ft., From . ft. to . ft.									
What is the nearest source of possible contamination:									
1 Septic tank ☒ 4 Lateral lines fuel 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? South How many feet? 10									
FROM		TO		LITHOLOGIC LOG		FROM		TO	
1.5		5		Varicolored, slightly plastic, silty to slightly very fine sandy CLAY.					
5		9		Reddish-brown, moderately plastic, fine sandy Clay.					
9		9.5		Limestone					
* Elevation determined from arbitrary benchmark									
Casing height & grout variances have been granted.									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/27/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 5/25/90 under the business name of Groundwater Technology by (signature) <i>[Signature]</i>									