

LOCATION OF WATER WELL: Fraction  $\frac{1}{4}$   $\frac{1}{4}$  NW  $\frac{1}{4}$  Section Number 3 Township Number T 15 S Range Number R 25 EW  
 County: Johnson

Distance and direction from nearest town or city street address of well if located within city?

WATER WELL OWNER: D. Bradley Hubbard  
 R#, St. Address, Box #: 3305 W. 191st St.  
 City, State, ZIP Code: Stillwell, KS. 66085  
 Board of Agriculture, Division of Water Resources  
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

	N	
	---	
	NW	NE
	X	
	---	
W		E
	SW	SE
	---	
	S	

DEPTH OF COMPLETED WELL: 250 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 140 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 60 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield 2 gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 10.5 in. to 250 ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)  
 7 Fiberglass  
 Blank casing diameter: 5 in. to 250 ft. Dia. in. to ft. Dia. in. to ft.  
 Casing height above land surface: 18 in. weight 5 lb 40 lbs/ft. Wall thickness or gauge No. 5 lb 40

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  
 10 Asbestos-cement  
 11 Other (specify)  
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 140 ft. to 150 ft. From ft. to ft.  
 From 230 ft. to 240 ft. From ft. to ft.  
 GRAVEL PACK INTERVALS: From 35 ft. to 250 ft. From ft. to ft.  
 From ft. to ft. From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 35 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? West How many feet? 150'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Clay			
8	55	Limestone			
55	60	Shale			
60	85	Limestone			
85	113	Shale			
113	120	Limestone water			
120	128	Shale			
128	140	Sandstone			
140	250	Shale			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/11/01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 595 This Water Well Record was completed on (mo/day/yr) 1/18/02 under the business name of Jesse Yoakum Well Drilling by (signature) Jesse Yoakum

OFFICE USE ONLY  
T  
R  
EW  
SEC