USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

County	Fraction	Section	number	Township number	Range number]
1. Location of well: Miami	NE 1/4 NE 1/4 NW 1/4	<u> </u>	9	1 15 s	R 2.5 E/X	_
2. Distance and direction from nearest town or city: 2 mi. Sw of 3. Owner of well: Foster L. wright R.R. or street: 11807 w. 54th						
Characteristics of well leasting if in aire 11 Car a accusate Car a			ote, zip code: Shawner, Kansas 66302			
4. Locate with "X" in section below: Sketch map:				6. Bore hole dia.		6
N	W Color			Well depth <u>30</u> と ft.		4
X 1 4eo	Now 69 High way	-		7 Cable tool X Rotary	Driven Dug Bored Reverse rotary	
W NK NE			ŀ	8. Use: X Domestic Public supply Industry		4
				Irrigation Air conditioning Stock		
SW SE 1				LawnOil field waterOther 9. Casing: Material Height: Above or below		
Septic 3				Threaded Welded Surface in.		
Septic That 200 From well				RMPPVC_X	Weightblss./ft	┨.
5. Type and color of material		Erom	_To	Dia. 5 in. to 202ft. dep	th gage No.	HC.
surface lime (brown, white)		ნ°™ 10	10 20	10. Screen: Manufacturer's n	ame RobinTech	.]
shale (green)			50	Type PVC	Dia. bin.	_
lime (brown)			62	Slot/SAUX-Grill/sl		-
shale (grey)			122	Set betweenft. c		:]
line (břeak @ 135)			152	Gravel pack? V = Size ra		4
shale (grey)			170	11. Static water level: 18 ft. below land sur	face Date 12/9/76	·
lime (soft) shale (greenish)		170 180	180 195	12. Pumping level below land		7
shale (red)			197	ft. after h		
shale (grey Green)			1 1	Estimated maximum yield	30gph ///	
lime (white)			212	13. Water sample submitted:	mo./day/yr	\cdot
shale (grey)			247	Yes X No 14. Well head completion:	Date	4
lime (2)9h/grey) shale (grey)			260	X Pitless adapter	Inches above grade	1
Shale (grey) lime (grey)			270 281	15. Well grouted? YES	Bentonite Concrete	
shale (dark grey)				Depth: From ft. to	15 ft.] (~
lime (soft)		281 282	298	16. Nearest source of possible	contamination:	10)
slate (black)		498	30 2	Well disinfected upon comple	.//*	
				17. Pump:	Not installed	1 10
		1		Manufacturer's name	HP 3/4 Volte 230	1 16
CASING DRILLED AND SLOTTED 15'-302'		ļ		3 1 1 2	ft. capacityg.p.m.	₹ 6
perioration size: 3/32"				Type: X Submersible	Turbine	
				Jet	Reciprocating	^v
(Use a second sheet if needed) 18. Elevation: 19. Remarks: Customer is aware of State reguleztiman well contractor's certification:						d !
account and agrees to install a 4' square				This well was drilled under m	y jurisdiction and this report	
Topography: re-enforced concrete platform around				is true to the best of my know		Z/3
——Hill COD OI WEII.			ľ	Business name	License No.	- 131
Upland XX				Address FE. W	annood in.	N N
Valley Signed Authorized representative						Z Z