


1 LOCATION OF WATER WELL: County: <u>Morris 064</u>	Fraction <u>NE 1/4 NW 1/4 SW 1/4</u>	Section Number <u>31</u>	Township Number <u>T 15 S</u>	Range Number <u>R 6 EW</u>
--	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3 Miles North of Delavan, KS

2 WATER WELL OWNER: <u>U. S. Corps of Engineers</u> RR#, St. Address, Box #: <u>700 Federal Building</u> City, State, ZIP Code: <u>601 E. 12th St. Kansas City, MO 64106-2895</u>	Board of Agriculture, Division of Water Resource Application Number:
---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>78.5</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>75</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>68</u> ft. below land surface measured on <u>1/25/95</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u><1</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>6</u> in. to <u>78.5</u> ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 11 Injection well 12 Other (Specify below) <u>Piezometer</u> Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>N/A</u> No
---	---

5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> 3 RMP (SR) 4 ABS Blank casing diameter <u>2</u> in. to <u>68.5</u> ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>36</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Sched 40</u>	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) Casing joints: Glued Clamped Welded Threaded <u>X</u>
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 Torch cut 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)	SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot <u>.010"</u> 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Saw cut 8 None (open hole)
SCREEN-PERFORATED INTERVALS: From <u>68.5</u> ft. to <u>78.5</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.	GRAVEL PACK INTERVALS: From <u>63.5</u> ft. to <u>78.5</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>Concrete</u> Grout Intervals: From <u>63.5</u> ft. to <u>58.5</u> ft. From <u>58.5</u> ft. to <u>3</u> ft. From <u>3</u> ft. to <u>0</u> ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) <u>Former DOD Airfield</u> Direction from well? <u>On site East of Maintenance Hangar</u> How many feet? <u>PERRIN AAF 100 feet</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Bark brown clay			
2	6	Grayish orange limestone			
6	11	Shale			
11	22	Claystone, yellow to gray			
22	28	Shale			
28	37	Claystone			
37	42	Pale orange limestone			
42	55	Dolomite			
55	66	Limestone			
66	70	Claystone			
70	78.5	Yellowish limestone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1/25/95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>555</u> This Water Well Record was completed on (mo/day/yr) <u>2/21/95</u> under the business name of <u>A.W. Pool, Inc.</u> by (signature) <u>Keith Pool</u>
