		WA	ATER WELL REC	ORD Form WWC-5	KSA 82a-1	1212 ID No)		
		TER WELL:	Fraction	SW	Sec	tion Number	Township Number	Range Nu	ımber
County:	LYON		5W 1/4	SW 1/4	1/4	6	T /6 S	R /0	EM
				ddress of well if located		•			
HWY5	6 LYON	10/NORN	es co. LIW	e, I MELE NO	RTW				
WATER	WELL OW	NER! MS NA	they 600,	0	, , , ,				
RR#, St. Ac	dress, Box	# : P. O. B	10× 73				Board of Agricultur	re, Division of Water	Resources
City, State,	ZIP Code	: Cour	V1 EL-600	12, KS. 6684	<u> </u>		Application Number		
LOCATE	WELL'S LO	CATION WITH	4 DEPTH OF C	OMPLETED WELL	46	ft. ELEVAT	ION:		
	SECTION		Depth(s) Groun	dwater Encountered	1 2.6	ft.	2	ft. 3	ft.
	N_		WELL'S STATIC	WATER LEVEL?	5 ft. belo	w land surface	e measured on mo/day/yr	4/13/06	
	i		Pun	np test data: Well wate	r was	ft. a	fter hou	irs pumping	gpm
	-NW -	- NE					8 Air conditioning 1		gpn
İ	1	1		3 Feedlot 6	Oil field water		9 Dewatering 1	,	low)
w_		 E	2 Irrigation	4 Industrial 7	Domestic (law	n & garden)	10 Monitoring well		
	i	i							
	-sw -	- SE	Was a chemica	l/bacteriological sample	submitted to I	Department? Y	es; If ye	es, mo/day/yrs sampl	le was sub
		1	mitted			Wa	ater Well Disinfected? Yes	s x 1	No
X									
TYPE	OF BLANK (CASING USED:		5 Wrought iron	8 Concre	ate tile	CASING JOINTS:	Glued Clamp	ed
1 Stee		3 RMP (S		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	9 Other	(specify below)		Welded	
2 PVC		4 ABS	,	7 Fiberglass				Threaded	
Blank casir	ng diameter	5	in. to	ft., Dia		in. to	ft., Dia	in. to	ft
Casing hei	ght above la	ınd surface	24	in., weight			lbs./ft. Wall thickness or	guage No. S.D.R. Z	<u> </u>
TYPE OF S	SCREEN OF	R PERFORATIO	ON MÁTERIAL:				10 Asbestos-	Cement	•
1 Stee	1 Steel 3 Stainless Steel 5 Fiberglass				8 RMP (SR) 11 Other (Specify)				
2 Bras	ss	4 Galvani	zed Steel	6 Concrete tile	9 AB	S	12 None use	d (open hole)	
SCREEN (OR PERFOR	RATION OPENI			zed wrapped		8 Saw cut	11 None (oper	n hole)
	tinuous slot		Mill slot		wrapped		9 Drilled holes 10 Other (specify)		44
2 Lou	vered shutte	r 41	key punched	7 Torc					
SCREEN-F	PERFORATI	ED INTERVALS	: From Z	ft. to	76	ft., From		ft. to	ft
,		CV INTEDVALO	From	ft. to	<i>II</i>	ft., From		ft. to	ft
,	SHAVELPA	CK INTERVALS	From	ft. to		ft., From		ft. to	ft
	JT MATERIA		at cement	2 Cement grout			1 Other		
Grout Inter	vals: From	m3	ft. to2.	5 ft., From	ft. t	о	ft., From		ft
What is the	e nearest so	urce of possible	e contamination:			10 Livest	•	4_Abautoned water	
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel storage		15 Oil well/Gas well	
2 Sev	2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)	
3 Wat	tertight sewe	er lines 6 See	page pit	9 Feedya	9 Feedyard		13 Insecticide storage		
Direction fr	rom well?	EAST				How man	y feet? /50		
FROM	TO		LITHOLOGIC	LOG	FROM	TO	PLUGGIN	IG INTERVALS	
0	21	CLAY.	BROWN						
21	32	CLAY G	DAY						
32	41	COAVA	LI .						
7	L.	20 1 4410 244	EDIO 0505	TION. TI				d under much to the	
							onstructed, or (3) plugge		
completed	on (mo/day/		25/06				cord is true to the best of ed on (mo/day/yr)		illet. Kansi
	Contractor: ousiness nar	_			i well hecord		(signature)		•••••
			>OCHATAL)	Descipol s	WL			pur	
							correct answers. Send top three		

records. Fee of \$5.00 for each constructed well.