4 11 00 1 = 1)	214/51:		TER WELL REC	ORD For			KSA 82a-12		ala Miraskaa	Dense Northern
_	ON OF WATER			NE	, CIA/			n Number		nip Number	Range Number
County:		on n nearest	NW 1/4 town or city street a		4 SW			20	Т	16 s	R 12 E
Distance and	u allection fron	ii nearest	town or city street a		Main, Ad			sas			
2 WATER	WELL OWNER	Roh	ert Mundy	- unu		0,					
			Road S5						Roard of	Agriculture D	vivision of Water Resources
O14 . C4-4- "	710 0-4-	. Adm	ira Kanese i	66830					Annlicati	an Niumbari	
LOCATE	WELL'S LOC	ATON WI	TH .						Applicati	on Number:	
3 AN "X" IN	N SECTION BO	OX:	DEPTH OF	COMPLETED	WELL		30	ft. ELEV	ATION:		3 Ft.
			Depth(s) Groun	ndwater Encour	ntered 1			ft.	2	ft.	3 Ft.
	N		1		-						ay/yr
A F											s pumping Gpm
	NW	- NE	Bore Hole Diar	Est. Yield Gpm: Well water was Ft. after Hours pumping Gp Bore Hole Diameter 8.625 In. to 30 Ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below							
Mile W		-	E WELL WATER	WELL WATER TO BE USED AS: 5 Public water supply						nditioning	11 Injection well
~ V	X		1 Domes	1 Domestic 3 Feed lot 6 Oil field water supply						tering	12 Other (Specify below)
	i		2 Irrigatio	on 4 Industri	ial 7 Lav	wn and	garde	n (domestic) 10 Mon	itoring well	MW-3R
	2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well MW-3R Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sa										
↓			Submitted	ar bacter lotogics	ai sample su	.Jiiille		•		nfected? Yes	
5 TYPE OF	F BLANK CAS	ING USE		F \A/	nt Iron	8 0	000004				
_				_	nt Iron						ued Clamped
1 Ste		_	IP (SR)		os-Cement	9 U	ıner (s	pecity belov	v)		elded
2 PV	С	4 AB	S	7 Fibergla	ass					Th	readed X
Blank casing	g diameter	2	In to	Ft., 8 Dia			In to		ft. Dia		in. toft.
Casing heig	ht above land	surface	FLUSH	in weight	SC	H 40	W				No
			TION MATERIAL:	III., WOIGHT _			7 lo	21/0	10	Asbestos-ce	ment
1 Ste	•		ainless steel	5 Fibergla	200		, F	RMP (SR) ABS	10		ý)
2 Bra			Ivanized steel	6 Concre	te tile		9 4	ABS	12	None used (open hole)
	R PERFORAT			2 00,1010	5 Gauze				8 Saw cu	,	11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes											
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 7 ft. to 30 ft. From ft. to ft.											
											t. to Ft.
SAN	ND PACK INTE	FRVALS:	From	5	ft. to	3	0	ft F			t. toFt.
المحا	AD I AOK IIVI	LINVALO.	From		ft. to		·		rom		t. to Ft.
	.,_\.		110111		11. 10	Т			10111		
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other											
Hekon	MA I EKIAL:	1 Ne	eat cement		ul	3	Ft.	лие	4 Other		
Grout Intervals From 3											
			ole contamination:				-	10 Livest			Abandoned water well
1 Septic tank								11 Fuels	storage	15	Oil well/ Gas well
2 Sewer lines			5 Cess pool	5 Cess pool 8 Sewage lagoon 12				12 Fertili	zer storage	16	Other (specify below)
3 Watertight sewer lines			6 Seepage p	,					ticide storag	_	Contaminated Site
Direction fro	•		- Coopago p					How many			
FROM	то	CODE	LITH	OLOGIC LOG		FR	ОМ	то		PLUGGING	SINTERVALS
0	.75		Concrete pav			+					
.75	3		Silty clay dar	k grav							
3	9		Olive gray sil								
9	20		Shale, olive g	ray, weath							
20	30		Shale, weath	ered light o	live gr						
30	TD		End of Boreh	ole							
										-104	
			11741-1								
						-					
		-				+					
						+					····
						_					
7 CONTR	ACTOR'S OR	LANDOW	NER'S CERTIFICA	ATION: This wa	ater well was	s (x) co	nstruc	ted, (2) reco	nstructed, c	r (3) plugged	under my jurisdiction and w
			09								ledge and belief. Kansas
										ompleted on (r	-
			Associ						v (signature	Bradlev	J. Johnson
under the business name of Associated Environmental, Inc. By (signature) Bradley J. Johnson INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka,											
			913-296-5545. Ser							P 10	1

C Y