

WATER WELL RECORD

Form WWC-5

FRANKLIN COUNTY
Division of Water Resources, App. No. 08-WW-FR-006

1 LOCATION OF WATER WELL:
County: FRANKLIN Fraction SW 1/4 SE 1/4 SW 1/4 Section Number 35 Township Number T 16 S Range Number R 17 EW

Distance and direction from nearest town or city street address of well if located within city? _____ **Global Positioning Systems** (decimal degrees, min. of 4 digits)
Latitude: 38.60878
Longitude: 95.50286
Elevation: 943
Datum: _____
Data Collection Method: _____

2 WATER WELL OWNER: JUOD RANCH
RR#, St. Address, Box # : ROUTE 1
City, State, ZIP Code : POMONA, KS 66076

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

	N	
-- NW --		-- NE --
-- SW --		-- SE --
	S	

4 DEPTH OF COMPLETED WELL 120 ft.

Depth(s) Groundwater Encountered (1) 45 ft. (2) ft. (3) ft.
WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr. 11/19/08
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield. 30 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr Sample was submitted Water well disinfected? Yes X No

5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
PVC 4 ABS 7 Fiberglass Threaded
Blank casing diameter 6 in. to 70 ft., Diameter in. to ft., Diameter in. to ft.
Casing height above land surface 30 in., Weight lbs./ft. Wall thickness or gauge No. SDR 26

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 70 ft. to 110 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 40 ft. to 120 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 40 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide storage 16 Other (specify below)
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/gas well BARN

Direction from well? WF ST How many feet? 34

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	CLAY			
5	8	SANDSTONE, ORANGE			
8	26	SHALE, GRAY			
26	29	SANDSTONE, ORANGE			
29	33	SHALE, BLACK FESSLE			
33	111	SANDSTONE			
111	121	SHALE, GRAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/19/08 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 760 This Water Well Record was completed on (mo/day/year) 3/11/09 under the business name of ASSOCIATED DRILLING PUMP by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.