


1 LOCATION OF WATER WELL: County: Franklin Fraction: SW 1/4 SW 1/4 SW 1/4 Section Number: 12 Township Number: T 16 S Range Number: R 18 **EW**
 Distance and direction from nearest town or city street address of well if located within city?
4 miles East and 4 miles North of Pomona Ks.

2 WATER WELL OWNER: Steven Powell Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: 3907 Idaho Application Number:
 City, State, ZIP Code: Pomona, KS 66076

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 47 ft. 2. 100 ft. 3. 100 ft.
 WELL'S STATIC WATER LEVEL 47 ft. below land surface measured on mo/day/yr 1-11-96
 Pump test data: Well water was 10 gpm after 7 7/8 hours pumping 10 gpm
 Est. Yield 10 gpm: Well water was 8 3/4 in. to 20 ft., and 7 7/8 in. to 20 ft.
 Bore Hole Diameter: 8 3/4 in. to 20 ft., and 7 7/8 in. to 20 ft.
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 90 ft., Dia. 200 PSI lbs./ft. Wall thickness or gauge No. 30
 Casing height above land surface 30 in., weight 200 PSI lbs./ft. Wall thickness or gauge No. 30
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 90 ft. to 100 ft., From 100 ft. to 100 ft.
 GRAVEL PACK INTERVALS: From 100 ft. to 200 ft., From 200 ft. to 200 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 20 ft. to 0 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NW How many feet? 40

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Soil			
2	12	Sandy soil			
12	58	Brown Sand			
58	78	Shale			
78	100	gray sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-11-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 561 This Water Well Record was completed on (mo/day/yr) 1-17-96 under the business name of Evans Energy Development, Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.