

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: FRANKLIN	NE 1/4 NE 1/4 NE 1/4	19	T 16 S	R 18 EW

Distance and direction from nearest town or city street address of well if located within city?

2 1/2 north of Pomona

2 WATER WELL OWNER: Ralph Wilson	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 3600 Colorado Rd.	Application Number:
City, State, ZIP Code: Pomona, KS 66076	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 180' ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 104' ft. below land surface measured on mo/day/yr 8/2/96. Pump test data: Well water was ft. after hours pumping gpm Est. Yield 15 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter .8 3/4 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	11 Injection well
Blank casing diameter 5" in. to 0-120' ft. Dia			12 Other (Specify below)
Casing height above land surface 24" in. weight 2.82 lbs./ft. Wall thickness or gauge No. 258			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 120 ft. to 180 ft.		
GRAVEL PACK INTERVALS:	From 24 ft. to 180 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 4 ft. to 24 ft.			
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? north			13 Insecticide storage	
			How many feet? 200'	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Clay-Brown			
4	15	Limestone-Yellow			
15	30	Shale-Black			
30	32	Limestone-Grey			
32	80	Shale-Grey			
80	91	Limestone-Grey			
91	110	Shale-Grey			
110	115	Sandstone-Grey			
115-130		Shale-Grey			
130	175	Sandstone-Grey			
175	180	Shale-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/2/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 8-22-96 under the business name of STRADER DRILLING CO., INC. by (signature) [Signature]
