ounty: FLANKLIN NW 1/4 NE 1/4 SW 1/4 Istance and direction from nearest town or city street address of well if located within city?	n Number   Township Number   Range Number
stance and direction from nearest town or city street address of well if located within city?  1000 W. 2 <sup>nd</sup> St.  WATER WELL OWNER: CHy of OHawa	
1000 W. 2nd St. WATER WELL OWNER: CHY of OHAWA	35   T 16 S   R 19 (EW)
WATER WELL OWNER: Crty of OHawa	TTALLA KC
	TTAWA , KS
R#, St. Address, Box # : 101 S. Hickory	
	Board of Agriculture, Division of Water Resources
ty, State, ZIP Code : Ottowa, KS	Application Number:
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL. 19.5  AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1. 9.5	ft. 2
	w land surface measured on mo/day/yr 6/23/98
Est. Yield gpm: Well water was	tt. after hours pumping gpm hours pumping gpm gpm
W	ft., and
WELL WATER TO BE USED AS: 5 Public water s	
	supply 9 Dewatering 12 Other (Specify below)
1 1 1 1	den only (1) Monitoring well
Was a chemical/bacteriological sample submitted to Depa	artment? YesNo; If yes, mo/day/yr sample was sub
S mitted	Water Well Disinfected? Yes No
TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete	tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (sp	pecify below) Welded
2 PVC 4 ABS 7 Fiberglass	Threaded
ank casing diameter O in. to 4 5 ft., Dia in. to	
asing height above land surface. FLUS. Hin., weight	lbs./ft. Wall thickness or gauge No. Sc. H 40
PE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP	(SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS	12 None used (open hole)
CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped	8 Saw cut 11 None (open hole)
1 Continuous slot (3) Mill slot 6 Wire wrapped	9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut	10 Other (specify)
CREEN-PERFORATED INTERVALS: From 4.5 ft. to 19.5	ft., From
_	ft., From
3A/10	
	ft., From
From ft. to	ft., From ft. to ft.
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite	$\omega$
rout Intervals From O ft. to 2 ft. 3 From ft. to.	
hat is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy	11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon	12 Fertilizer storage (36 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard	13 Insecticide storage CONTAMINATED SITE
rection from well?	How many feet?
FROM TO LITHOLOGIC LOG FROM	TO PLUGGING INTERVALS
O. I', Organic Black Topsoil	
1 3 Gravel SAND Sitt Fill Material	
3' 5' Clay Brown	
5' 7' Brick: Gravel Fill Material	
10' 19.5 Clay, Brown	
10' 19.5 Clay Brown	
10' 19.5 Clay, Brown	
10' 19.5 Clay, Brown	
10' 19.57 Clay, Brown	
10' 19.5 Clay, Brown	
10' 19.5 Clay, Brown	
10' 19.5 Clay, Brown	
10' 19.5 Clay, Brown	
10' 19.5 Clay, Brown	
10' 19.57 Clay, Brown 19.51 TD End of Borehole	d (2) reconstructed or (3) plugged under my jurisdiction and was
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed	d, (2) reconstructed, or (3) plugged under my jurisdiction and was did this record is true to the best of my knowledge and belief. Kansag

INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the orrect answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.