WATE	R WEI	LL RECORD Mw-2 Form WWC-5 Division of Water Resources App. No.	
		OF WATER WELL: Fraction Section Number Township No. Range Number	
	ty: Fra		
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here			
1		ely 2.530' N and 120' W of Highway 68 and Indiana Longitude: 95.36067. (in decimal degrees)	
, , ,		of Ottawa.  Datum: WGS 84, NAD 83, NAD 27	
		ELL OWNER: BNSF Railway Co. Collection Method:	
		Address, Box #: 4515 Kansas Ave  IP Code : Kansas City KS 66106  GPS unit (Make/Model: Garmin Geko 201  Digital Map/Photo,  Topographic Map,  Land Survey	
City	, siate, Z	IP Code : Kansas Citv. KS 66106 ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m	
3 LOC		LL.	
	H AN "X FION BC	****	
WELL'S STATIC WATER LEVEL. unknownft. below land surface measured on mo/day/yr.			
Pump test data: Well water was			
W   N\	V	EST. YIELDgpm. Well water wasft. afterhours pumpinggpm  Bore Hole Diameter 12in. to .21.5ft., and .6in. to .45ft.	
"		WELL WATER TO BE USED AS: Public water supply Geothermal Injection well	
sv	v   s	E Domestic Feedlot Oil field water supply Dewatering Other (Specify below)	
		☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well	
	S	If yes, mo/day/yr sample was submitted	
	1 mile	Water well disinfected? ☐ Yes ☑ No	
		SING USED: Steel PVC Other	
CASING JOINTS: Glued Clamped Welded Threaded			
Casing diameter .2.049 in. to .24 ft., Diameter .7.943 in. to .21.5 ft., Diameter in. to ft. Casing height above land surface .0 in., Weight 0,682/5.305 lbs./ft., Wall thickness or gauge No0.163 / 0.341"			
TYPE	OF SCRI	EEN OR PERFORATION MATERIAL:	
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)			
SCREEN OR PERFORATION OPENINGS ARE:			
☐ Continuous slot   ☑ Mill slot   ☐ Gauze wrapped   ☐ Torch cut   ☐ Drilled holes   ☐ None (open hole) ☐ Louvered shutter   ☐ Key punched   ☐ Wire wrapped   ☐ Saw cut   ☐ Other (specify)			
SCREE	N-PERF	ORATED INTERVALS: From	
		Fromft. toft. From	
	GRAV	EL PACK INTERVALS: From	
6 GRO	UT MA	TERIAL: Neat cement Cement grout Dentonite Other	
Grout Intervals: From .0			
Grout Intervals: From .0			
	Sewer lin	nes	
		ht sewer lines  Seepage pit Feedyard Fertilizer storage Oil well/gas well railcar release  n well E Distance from well approximately 190'	
0	10	Clay, moist	
10	21.5	Clay, friable	
21	7.5	Gray Shale W/ Didok laminations	
7 CON	TRACT	OR'S OR LANDOWNER'S CERTIFICATION: This water well was 🛛 constructed, 🗆 reconstructed, or 🔲 plugged	
under m	y jurisdi	ction and was completed on (mo/day/year) .1/.12/09 and this record is true to the best of my knowledge and belief.	
0 10 Clay, moist 10 21.5 Clay, friable 21.5 27 Brown, coarse sandstone 27 45 Gray shale w/ black laminations  7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) .1/12/09			
INSTRUC	CTIONS:	Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three conjugations are conjugated by the correct answers.	
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367 Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at			
http://www	http://www.kdheks.gov/waterwell/index.html.		
K5A 82a	-1212	Check: White Copy, Blue Copy, Pink Co	