		RECORD		C-5	Divisio	n of Wa	ater Reso	urces: Ap	p. No.			
1		WATER WELL:			Sec	tion N	umber	Townsh	nip Number	Range Number		
County:	t nd dispostio	ranklin	NW 14 NW 1/2	NW	4 Clab	<u>36</u>	.,.	T	16 s	R 19 E		
Distance and direction from nearest town or city street address of well if Clobal Positioning System (decimal degrees. min. of 4 digits) located within city? 104 E Logan St, Ottawa, KS 66067  Latitude: NA												
Longitude: NA												
2 WATER WELL OWNER: KDHE (Baxter Oil)						Elevation: TOC: 891.14; RIM: 891.49						
RR#. S	RR#, St. Address, Box # : 1000 SW Jackson						Datum: NAVD 88					
City, S	City, State, ZIP Code : Topeka, KS, 66612						Data Collection Method: legal survey					
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 18 ft.												
LOCA	TON				M	1W4						
WITH	AN "X" I	N Depth(s) Groun	dwater Encountere	d1			ft. 2		ft. 3	ft.		
SECT	ION BOX:	WELL'S STAT	TIC WATER LEVE	L 5.66	ft. be	elow la	nd surfa	ce measu	red on mo/d	ay/yr 1/27/10		
	N	Pump	test data: Well w	ater was		ft.	after		hours pumpi	ng gpm		
XI	Pump test data: Well water was ft. after hours pumping gp Est. Yield gpm: Well water was ft. after hours pumping gp											
⊢nw	NW NE WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well											
	1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)											
W 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well												
- sw - sE -												
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs												
S Sample was submitted Water Well Disinfected? Yes No X												
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  (2) PVC 4 ABS 7 Fiberglass Threaded X  Blank casing diameter 2 in. to 3 ft., Dia in. to ft., Dia in. to ft.  Casing height below land surface 0.35 ft., Weight lbs./ft. Wall thickness or gauge No.												
1 Ste	or Cash	RMP(SR) 6	A chestos-Cement	0 C0	her (cne	cify be	, CASI	ind join	Walda	d Clamped		
2 DV	C	A A DC 7	Fibergless	<i>y</i> 01.	ner (spe	chy be	iow)		Throad	u lad W		
Plank and	Threaded X											
Diank casing manifele 4 in to 5 it., Dia in to It., Dia in to It.												
Casing height below land surface 0.35 ft., Weight lbs./ft. Wall thickness or gauge No.  TYPE OF SCREEN OR PERFORATION MATERIAL:												
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ARS 11 Other (specific)												
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)												
INCREEN UR PERFURATIUN OPENINON ARE:												
1 Continuous slot (3) Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)												
1 Continuous slot (3) Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  SCREEN-PERFORATED INTERVALS: From 3 ft. to 18 ft. From ft. to ft.												
SCREEN-	PERFORA	TED INTERVALS:	From 3	It. to	o]	18	tt. Fro	om	ft. to	ft.		
-			From	ft. to	)		tt. Fro	om	tt. to	)		
From ft. to ft. From ft. to  GRAVEL PACK INTERVALS: From 2 ft. to 18 ft. From ft. to  From ft. to ft. From ft. to									)tt.			
			From	tt. to	o 		tt. Fro	om	ft. to	) ft.		
6 GROU	T MATE	RIAL: 1 Neat cem	ent 2 Cement gro	out (3 🎝	Bentonite	e (4	1)Other	Concret	e: 0-1ft			
Grout Inte	rvals Fi	om 1 ft. to	2 ft. From		ft. to	_	ft.	From		ft. to ft.		
What is the	e nearest so	urce of possible con	tamination:		•	,			·			
	ic tank		nes 7 Pit privy		vestock j			cticide S		16 Other (specify		
	er lines	5 Cess pool							vater well	below)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well												
Direction 1	from well?	SW		How r	nany fee	et? _~7:	5 ft		· • • • • • • • • • • • • • • • • • • •			
FROM	TO	LITHO	DLOGIC LOG		FROM	TO		LI	THOLOGIC	LOG		
0	3	Grass, topsoil; Brown s	·····	el, some	18		Limestor					
		sand, mod. plasticity										
3	4	Brown, mottled shades										
	· · · · · · · · · · · · · · · · · · ·	gravel and limestone gr										
4	9	Dark gray brown silty o	clay, with very fine san	d, mod.								
-	14	plasticity										
9	14	Dark gray brown gradi		with very			!					
14	18	fine sand, mod. plasticit Brown, silty clay, with	<del></del>	asticity			Flushm	lount wa	iver from B	OW		
fine gravel at base							X 1431111	IOUIL WA	iver moni B	<u> </u>		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged												
under my jurisdiction and was completed on (mo/day/year)  Kansas Water Well Contractor's License No. 757  This Water Well Record was completed on (mo/day/year) 3/3/10												
		tractor's License No.					ompleted	on (m <b>o</b> /c	y (year) 3	/3/10		
		of Larsen & Asso			ignature)			1	in Jurean	·		
INSTRUCT	IONS: Please	fill in blanks or circle the	e correct answers. Send	top three co	pies to Ka	insas De	partment o	of Health ar	d Environment	Bureau of Water.		
your records.	Fee of \$5.00	Jackson St., Suite 420, T for each constructed well	l. Visit us at http://www	kdheks.gov	/waterwel	.90-3322 11.	. sena on	ic to WAIL	K WELL UWN	iek and retain one for		