1 LOCATION OF WATER WELL:	WATER WELL RECORD	Form WWC-5 KSA 82a- Section Number		Dongs Ni
<u></u>	l .			Range Number
			т <b>16</b> s	R 20 E
Distance and direction from nearest town or city street address of well if located within city?  3300 K-68 Highway, Ottawa, KS				
2 WATER WELL OWNER: Wal-Mar				
RR#, St. Address, Box # : 2101 SE			Decad of Apple there Die	laian af Matan Danasan
City, State, ZIP Code : Bentony				ision of Water Resources
LOCATE WELL'S LOCATON WITH	fille, Arkalisas /2/10		Application Number:	
3 AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL	15 ft. ELE	VATION: RIM 943.	28/TOC 943.01
N D	DEPTH OF COMPLETED WELL Depth(s) Groundwater Encountered 1. VELL'S STATIC WATER LEVEL	.5 <b>5.5</b>	t 2 ft	3 Ft C
4	MELL'S STATIC WATER LEVEL	9.08 # bolowland	curfoce maccured on moldovi	11/12/12
			Ft. after hours p	oumping
± W E B	est. Yield Gpm: Well water	er was	Ft. after Hours (	oumping
	Bore Hole Diameter 8.625 In. to	15	ft. and ir	n. to Ft. S
	VELL WATER TO BE USED AS: 5 1 Domestic 3 Feed lot 6	Public water supply	8 Air conditioning 1	1 Injection well
SW SE				
<b>                 </b>	2 Irrigation 4 Industrial 7			
y S	Vas a chemical/bacteriological sample	submitted to Department?	Yes No <b>X</b> If yes,	mo/day/yr sample was
1 3 1	Submitted		ater Well Disinfected? Yes	
5 TYPE OF BLANK CASING USED:	5 Wrought Iron		CASING JOINTS: Glue	
1 Steel 3 RMP (SF		nt 9 Other (specify belo		
2 PVC 4 ABS	•	```	,	aded X
	7 Fiberglass			
Blank casing diameter i	Ft., in. to <b>5</b> Dia	In. to	ft. Dia	in to ft
Casing height above land surface	FLUSH In weight	SCH 40 Lbe /fi	Wall thickness or gauge No	11. 10
TYPE OF SCREEN OR PERFORATION			10 Asbestos-ceme	
1 Steel 3 Stainless 2 Brass 4 Galvaniz	s steel 5 Fiberglass ted steel 6 Concrete tile	0 KMP (SK)	11 Other (specify)	an hole)
SCREEN OR PERFORATION OPENINGS		9 ABS zed wrapped	12 None used (ope 8 Saw cut	
i <u>—</u>	lill slot 6 Wire			11 None (open noie)
			9 Drilled holes	
2 Louvered shutter 4 Ke		on cut	10 Other (specify)	•••••
SCREEN-PERFORATED INTERVALS:				
	Fromft. to	ft.	Fromft. t	oFt. 🛪
SAND PACK INTERVALS:	From 3 ft. to	<b>15</b> ft.	From ft. t	oFt.
	From ft. to	ft.	From ft t	o Et
6 GROUT MATERIAL: 1 Neat cen	ment 2 Cement grout	3 Bentonite	4 Other	
	Ft.	Ft.		
Grout Intervals From2 0.5 ft.	to 1 From3	1 to 3	ft. From	ft. toft.
What is the nearest source of possible cor	ntamination:			andoned water well
1 Septic tank 4	Lateral lines 7 Pit priv	y 11 Fuel	storage 15 Oil	well/ Gas well
2 Sewer lines 5	Cess pool 8 Sewage			er (specify below)
3 Watertight sewer lines 6	Seepage pit 9 Feedya	ard 13 Insec		ntaminated Site
Direction from well?	coopage p.	How many	•	l l
FROM TO CODE	LITHOLOGIC LOG	FROM TO	PLUGGING IN	ITED\/ALS
	crete and Gravel fill materi		FEOGOING IN	
	Clay, dark yellowish brow			
	le, black, highly weathered			
	of Borehole			
TO TO ENG	OI BOICHOIC			
7 CONTRACTOR'S OR LANDOWNER'S	CERTIFICATION: This water well w	as (x) constructed. (2) reco	onstructed, or (3) plugged und	er my jurisdiction and w
Completed on (mo/day/yr)				
Water Well Contractor's License No.	585	This Water Well D	ecord was completed on (mo/	day/yr) 11/21/12
under the husiness same of	Associated Environment		By (signature) <b>Bradley J.</b>	
under the business name of INSTRUCTIONS: Please fill in blanks a	and circle the correct answers. Send three	copies to Kansas Denartmen	of Health and Environment Ru	A Lot Water Joneka
Kansas 66620-0001. Telephone: 913-2	96-5545. Send one to WATER WELL OV	VNER and retain one for your	records.	