

MW-2s 2311031 WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Dickinson NE 1/4 NE 1/4 NE 1/4 Section Number 3 Township Number T 16 S Range Number R 3 E/W

Distance and direction from nearest town or city street address of well if located within city? N. Main, Hope KS

2 WATER WELL OWNER: RR#, St. Address, Box #: North Central Kansas Coop PO Box 157 Hope KS 67451 City, State, ZIP Code: Application Number: Board of Agriculture, Division of Water Resources

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NE corner]

4 DEPTH OF COMPLETED WELL: 54.0 ft. ELEVATION: 1378.04

Depth(s) Groundwater Encountered: 1. 20 ft. 2. 23.20 ft. below land surface measured on mo/day/yr 2-22-96

WELL'S STATIC WATER LEVEL: 23.20 ft. below land surface measured on mo/day/yr 2-22-96

Pump test data: Well water was ... ft. after ... hours pumping ... gpm

Est. Yield ... gpm Well water was ... ft. after ... hours pumping ... gpm

Bore Hole Diameter: 8 in. to ... ft., and ... in. to ... ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes ... No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ... No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ... Clamped ...

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ... Threaded ... Flush

Blank casing diameter: 2 in. to ... ft., Dia ... in. to ... ft., Dia ... in. to ... ft.

Casing height above land surface: 2.51 in., weight ... lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 43.5 ft. to 53.5 ft. From ... ft. to ... ft.

GRAVEL PACK INTERVALS: From 41 ft. to 54 ft. From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 41 ft. to 3.0 ft. From ... ft. to ... ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

D.O 53 Clay

53.0 54 Shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-22-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 3-15-96 under the business name of GSI by (signature) Alison J. Irwin

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.