


LOCATION OF WATER WELL: County: Dickenson Fraction: SW 1/4 SW 1/4 SW 1/4 Section Number: 14 Township Number: T 16 S Range Number: R 4 E

Distance and direction from nearest town or city street address of well if located within city?  
1/2 W 1/4 S Herrington

WATER WELL OWNER: Jerry Meyer  
 RR#, St. Address, Box #: RR 3 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Herrington, KS 67449 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: 272 ft. ELEVATION: 6-22-89



Depth(s) Groundwater Encountered: 1 ft. 2. 2 ft. 3. 3 ft.  
 WELL'S STATIC WATER LEVEL: 522 ft. below land surface measured on mo/day/yr 6-22-89  
 Pump test data: Well water was 30 gpm Well water was 10 ft. after 7 hours pumping 27 gpm  
 Est. Yield 30 gpm Well water was 10 ft. after 7 hours pumping 27 gpm  
 Bore Hole Diameter: 9 in. to 10 ft., and 7 in. to 27 ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No X

TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded

Blank casing diameter: 5 in. to 67 ft., Dia. in. to 160 lbs./ft. Wall thickness or gauge No. 2.14

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 27 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 67 ft. to 27 ft., From 10 ft. to 27 ft., From 10 ft. to 27 ft., From 10 ft. to 27 ft.

GRAVEL PACK INTERVALS: From 10 ft. to 27 ft., From 10 ft. to 27 ft., From 10 ft. to 27 ft., From 10 ft. to 27 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 10 ft., From 10 ft. to 27 ft., From 10 ft. to 27 ft., From 10 ft. to 27 ft.

What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage

Direction from well? NE How many feet? 50 +

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	Clay			
4	22	limestone			
22	40	Yellow Shale + lime			
40	55	Red Shale			
55	27	lime			
27	23	Water			
23	27	Shale			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-25-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 120 This Water Well Record was completed on (mo/day/yr) 6-25-89 under the business name of Backhoe Drilling by (signature) Paul Backhoe

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 16 R 4 E SW 1/4 SW 1/4 SW 1/4