WATER WEI	LL RECORD	Form V	VWC-5	Di	ivision of Water	Resources App. No	).	
1 LOCATION OF WATER WELL:		Fraction		Secti	on Number	Township No.	Range Number	
County: Di	ckinson	1/4 <b>NW</b> 1/4				T 16 S	R 4 X E □W	
Street/Rural Address of Well Location; if unknown, distance & direction						System (GPS) in		
from nearest town or intersection: If at owner's address, check here $\square$ .					Latitude: (in decimal degrees)			
1/2 mile North of Herington, KS					Longitude: (in decimal degrees) Elevation:			
			Datur	ation:	L D NAD 83 D	 NAD 27		
2 WATER WELL OWNER: Herington School					<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method:			
RR#, Street Address, Box #: c/o Commercial Mechanical					GPS unit (Make/Model:)			
City, State, ZIP Code : 1655 Wabash				_ D !	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey  Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
A VOCATE WI	Wichit				5-15 m, ∐ >15 m			
3 LOCATE WE WITH AN "X	"IN 4 DEPTH OF	COMPLETED WE	LL 300		ft	x 90 holes		
SECTION BO								
N	WELL'S STATIC WATER LEVEL68ft. below land surface measured on mo/day/yr.5/30/11							
	Pump test data: Well water wasft. after hours pumping gpm							
EST. YIELD. <b>n/a</b> gpm. Well water was								
W								
	WELL WATER	TO BE USED AS:	☐ Public wa	ter supp	ly 🔼 Geo	othermal I	njection well	
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
S						103 203 110		
S If yes, mo/day/yr sample was submitted Water well disinfected? X Yes No								
5 TYPE OF CASING USED: Steel PVC XX Other Polyethylene								
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to Summer in. to Summ								
Casing height above land surface. 0 in., Weight								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
Brass	Galvanized Steel		hole)					
SCREEN OR PERFORATION OPENINGS ARE:  Continuous slot								
Louvered shutter Key punched Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other  Grout Intervals: From 0 ft. to 300 ft., From ft. to ft., From ft. to ft.								
	est source of possible conta	mination:	m	π. το	n.,	From	. ft. toft.	
Septic ta		es Pit privy	Livestock	nens	☐ Insecticide	storage \( \square \) Oth	er (specify below)	
☐ Sewer lin	nes	Sewage lagoon	☐ Fuel storag		Abandoned		or (specify below)	
	ht sewer lines	•	Fertilizer s		Oil well/gas	s well		
FROM TO <b>3</b>	LITHOLOG Topsoil	IC LOG	FROM	TO	LITHO. LC	OG (cont.) or PLU	GGING INTERVALS	
3 5	Clay, brown							
5 40	Limestone		+					
40 85	Shale, gray							
85 95	Limestone w/fract	ure at 83'						
95 215	Shale, hard gray							
215 300	Shale, gray w/lin	estone layers						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) August 7, 2011 this record is true to the best of pay knowledge and belief								
Kansas Water Well Contractor's License No138 This Water Well Record was completed of any day year) 9/7/11								
under the business name of Peterson . Irrigation, Inc by (signature) by (signature) by (signature) by (signature) Send three copies								
(white, blue, pink) to	o Kansas Department of Health	and Environment, Bureau	of Water, Geol	ogy Section	on, 1000 SW Jack	kson St., Suite 420, T	oneka, Kansas 66612-1367	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.  KSA 823-1212								
KSA 82a-1212								