

MW-6

1 LOCATION OF WATER WELL: County: <u>Dickinson</u>	Fraction: <u>NE 1/4 SW 1/4 SW 1/4</u>	Section Number: <u>12</u>	Township Number: <u>T 16 S</u>	Range Number: <u>R 4 E/W</u>
---	---------------------------------------	---------------------------	--------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city? 1st 3rd Walnut

2 WATER WELL OWNER: <u>DATE-BER</u> RR#, St. Address, Box #: <u>Forkes Field Bldg 740</u> City, State, ZIP Code: <u>Topeka, KS 66620-0001</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>35</u> ft. ELEVATION: <u>—</u>
--	--

Depth(s) Groundwater Encountered 1. ~ 30 ft. 2. — ft. 3. — ft.

WELL'S STATIC WATER LEVEL 15.37 ft. below land surface measured on mo/day/yr 8/27/98

Pump test data: Well water was — ft. after — hours pumping — gpm

Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm

Bore Hole Diameter 8.625 in. to 35 ft., and — in. to — ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well <u>MW-6</u>	

Was a chemical/bacteriological sample submitted to Department? Yes — No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes — No X

5 TYPE OF BLANK CASING USED:	3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>—</u> Clamped <u>—</u>
------------------------------	----------------	-----------------	--

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded —

2 PVC 4 ABS 7 Fiberglass Threaded X

Blank casing diameter 2 in. to 25 ft. Dia. — in. to — ft. Dia. — in. to — ft.

Casing height above land surface Flush 0 in. weight SCH 40 lbs./ft. Wall thickness or gauge No. —

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 35 ft. to 25 ft. From — ft. to — ft.

GRAVEL PACK INTERVALS: From 35 ft. to 24 ft. From — ft. to — ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

Grout Intervals: From 24 ft. to 22 ft. From 22 ft. to 0 ft. From — ft. to — ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>Contaminated site</u>

Direction from well? —

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Asphalt			
6	1	clay w/ some silt			
1	35	limestone			
35	TD	end of borehole			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>1</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8/24/98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>585</u> This Water Well Record was completed on (mo/day/yr) <u>9/3/98</u> under the business name of <u>ASL</u> by (signature) <u>Adrian G. Duran</u>
--