

1 LOCATION OF WATER WELL: County: <u>Morris</u>	Fraction <u>NE 1/4 SE 1/4 SE 1/4</u>	Section Number <u>3</u>	Township Number T <u>16</u> S	Range Number R <u>5</u> E/W
--	---	----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

From Herington 4 mi east 1/2 mi North west side road

2 WATER WELL OWNER: <u>Paulettes Park</u> RR#, St. Address, Box # : <u>2800 Rd,</u> City, State, ZIP Code : <u>Herington, KS, 67449</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>60</u> ft. ELEVATION:
--	---

1 Mile

Depth(s) Groundwater Encountered 1. 34 ft. 2. 34 ft. 3. 34 ft.

WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 35 ft. after 55" min pumping 60 gpm

Est. Yield 30 gpm Well water was 51 ft. after 2 hours pumping 40 gpm

Bore Hole Diameter 8 in. to 60 ft. and 60 in. to 60 ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: <u>Glued</u> Clamped
------------------------------	----------------	-----------------	-------------------------------------

1 Steel

2 PVC

Blank casing diameter 5 in. to 40 ft. Dia 40 in. to 40 ft. Dia 40 in. to 40 ft.

Casing height above land surface 18 in., weight SDR-26 160 lbs./ft. Wall thickness or gauge No.

3 RMP (SR)

4 ABS

6 Asbestos-Cement

7 Fiberglass

9 Other (specify below)

Welded

Threaded

TYPE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-cement
---	--------------------

1 Steel

2 Brass

3 Stainless steel

4 Galvanized steel

5 Fiberglass

6 Concrete tile

8 RMP (SR)

9 ABS

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

2 Louvered shutter

3 Mill slot

4 Key punched

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS:	From <u>40</u> ft. to <u>60</u> ft.	From <u>40</u> ft. to <u>60</u> ft.	From <u>40</u> ft. to <u>60</u> ft.
------------------------------	-------------------------------------	-------------------------------------	-------------------------------------

GRAVEL PACK INTERVALS:	From <u>30</u> ft. to <u>60</u> ft.	From <u>30</u> ft. to <u>60</u> ft.	From <u>30</u> ft. to <u>60</u> ft.
------------------------	-------------------------------------	-------------------------------------	-------------------------------------

6 GROUT MATERIAL:	1 Neat cement	2 Bentonite	4 Other
-------------------	---------------	-------------	---------

Grout Intervals: From 4 ft. to 25 ft. From 25 ft. to 30 ft. From 30 ft. to 30 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? 1000

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>3</u>	<u>Top Soil</u>			
<u>3</u>	<u>18</u>	<u>yellow limestone soft</u>			
<u>18</u>	<u>23</u>	<u>yellow-tan limestone Hard</u>			
<u>23</u>	<u>31</u>	<u>Red clay shale</u>			
<u>31</u>	<u>45</u>	<u>Tan limestone layered</u>			
<u>45</u>	<u>60</u>	<u>Blue clay shale</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-10-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>513</u> This Water Well Record was completed on (mo/day/yr) <u>4-1-98</u> under the business name of <u>H2O Drilling Service</u> by (signature) <u>Mary Schneider</u>
--