


1 LOCATION OF WATER WELL: County: Morris Fraction: NW 1/4 NE 1/4 NE 1/4 Section Number: 28 Township Number: T 16 S Range Number: R 6 EW

Distance and direction from nearest town or city street address of well if located within city?  
1 South & 2 E of Delevan

2 WATER WELL OWNER: Elwood Orr  
 RR#, St. Address, Box #: White City, Ks 66872  
 City, State, ZIP Code: White City, Ks 66872  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 79 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 70 ft. below land surface measured on mo/day/yr Sep 3-90  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield 20+ gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 8 in. to 24 ft., and 6 1/2 in. to 100 ft.  
 WELL WATER TO BE USED AS:  
 Domestic  Feedlot  Oil field water supply  Dewatering  Other (Specify below)  
 Irrigation  Industrial  Lawn and garden only  Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No  If yes, mo/day/yr sample was submitted  
 Water Well Disinfected?  Yes No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued  Clamped  
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter: 5 in. to 70 ft., Dia. in. to ft., Dia. in. to ft.  
 Casing height above land surface: 16 in., weight lbs./ft. Wall thickness or gauge No. SPR-26  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 70 ft. to 100 ft. From ft. to ft.  
 GRAVEL PACK INTERVALS: From NONE ft. to ft. From ft. to ft.

6 GROUT MATERIAL:  Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout intervals: From 3 ft. to 24 ft. From ft. to ft. From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage Barn  
 Direction from well? North West How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil Blk	78	100	LIME Gray-upper Frac.
2	3	Clay Brn			
3	10	LIME TAN			
10	23	LIME TAN Frac			
13	23	LIME TAN			
23	32	Shale TAN			
32	34	LIME TAN			
34	37	Shale Green			
37	38	LIME			
38	47	Red Rock			
47	56	Shale Gray			
56	64	LIME Gray			
64	67	Shale Gray			
67	74	LIME Gray			
74	78	Shale Gray lite			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  constructed,  reconstructed, or  plugged under my jurisdiction and was completed on (mo/day/year) Sep 3 90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 218 This Water Well Record was completed on (mo/day/yr) Oct 28 90 under the business name of ZINN Water Well Drlg by (signature) Joseph A Zinn

OFFICE USE ONLY

T

R

EW

SEC

1/4

1/4

1/4