County: Morris Fraction SE NW NW Sec. 6 T 16 S R 6 EW
CORRECTION(S) TO WATER WELL COMPLETION RECORD (WWC-5) (to rectify lacking or incorrect information)
Owner: Hodgdon Powder Company
Location was listed as: Location changed to:
Section-Township-Range: 6-165-5E 6-165-6E
Section-Township-Range: 6-165-5E 6-165-6E Fraction (½½½): SE NW NW SE NW NW
Other changes: Initial statements:
Changed to:
Comments:
Verification method: Written & legal descriptions, well owner's address, area road map, and mapping tool on KGS website. Submitted by: Kansas Geological Survey Data Resources Library 1930 Constant Ave. Lawrence KS 660473726
initials: 12/14/2016
Submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 660473726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

			WA1	TER WELL RECORD F		-5 KSA 82			
		ATER WELL:	Fraction			ection Number			Range Number
	Morris		SE 3		1/4	6	T 16	<u>s</u>	R 5 (E)W
		on from nearest to Rd., Morris Co		t address of well if locate	d within city	y?			
2 WATE	R WELL O	WNER: Hodgde	on Powder C	ompany					
		ox# : 2577 Q					Board of Agricult	ure, Divis	sion of Water Resources
City, State	e, ZIP Code	Hering	ton, Kansas	67449			Application Numb		
3 LOCAT	E WELL'S	LOCATION	4 DEPTH OF	COMPLETED WELL	18	ft. ELEV	/ATION:		
WITH		SECTION BOX: N	Depth(s) Grou	ndwater Encountered 1.	19	0 ft.	2	ft.	3 ft
∓ г									/r
	Y		1						npinggpm
	/NW	NE	Est Yield !	A gpm: Well water	was	ft. a	fter h	ours pur	mpinggpm
W Wile	!		Bore Hole Diar	meter11 in. to .	18.	5 ft.,	and	<u></u> in	. to ft.
_ M		 	WELL WATER	R TO BE USED AS: 5 F	Public wate	r supply	8 Air conditioning	(11)	Injection well
	_!		1 Domesti	c 3 Feedlot 6 0	Dil field wat	er supply	9 Dewatering	12	Other (Specify below)
,	~ ~ SW ~ ~	SE	2 Irrigation	n 4 Industrial 7 i	awn and g	arden only	10 Monitoring well		
			Was a chemic	al/bacteriological sample	submitted (mo/day/yr sample was
1		S	submitted			Wa	ater Well Disinfected	? Yes	No_ √
5 TYPE	OF BLANK	CASING USED:	-	5 Wrought iron	8 Conc	rete tile	CASING JOIN		iClamped
s		3 RMP (SI	R)	6 Asbestos-Cement	9 Other	(specify belo	ow)	Weld	ed
(2)°		4 ABS		7 Fiberglass					aded. 🗸
Blank cas	ing diamete	r	in. to	. 8 , ft., Dia	in.	to	ft., Dia		. in. to ft.
Casing he	ight above I	and surface	. 2.5	. in., weight		lbs./	ft. Wall thickness or	gauge N	lo
TYPE OF	SCREEN C	R PERFORATIO	N MATERIAL		7 PV	/C	10 Asbes	tos-ceme	ent
1 S	teel	3 Stainless	s steel	5 Fiberglass	8 RN	MP (SR)	11 Other	(specify)) <i></i>
2 B	rass	4 Galvaniz	ed steel	6 Concrete tile	9 AE	S	12 None	used (op	en hole)
SCREEN	OR PERFO	RATION OPENIN	IGS ARE:	5 Gauzed	wrapped		8 Saw cut		11 None (open hole)
1 C	ontinuous s	slot (3)M	fill slot	6 Wire w	apped		9 Drilled holes		
2 L	ouvered shu	utter 4 K	(ey punched	7 Torch o					
SCREEN-	PERFORA1	TED INTERVALS:							to ft
			From	ft. to		ft., Fr	om	ft.	to ft.
	RAVEL PA	CK INTERVALS:							to ft
						ft., Fr	om	ft.	to ft
	T MATERIA			2 Cement grout	3 Bento				
Grout Inte	rvals: Fro	m 2.5	.ft. to	ft., From	ft.	to	$\dots . ft, \ From \dots$		ft. to ft.
What is th	e nearest s	ource of possible	contamination:			10 Lives	stock pens	14 A	bandoned water well
1 Sep	tic tank	4 Late	ral lines	7 Pit privy		11 Fuel	storage	15 O	il well/Gas well
2 Sew	er lines	5 Cess	s pool	8 Sewage lagoo	n	12 Ferti	lizer storage	16 O	ther (specify below)
3 Wat	ertight sewe	erlines 6 Seep	page pit	9 Feedyard	13 Insectici		icide storage		
Direction	from well?					How man	ny feet?		
FROM	TO		LITHOLOGIC		FROM	ТО	PLUC	GING IN	MERVALS
0	0.5	Clay topsoil,		rown					
0.5	6.5	Clay, silty, Da							
6.5		Limestone, Y							
17.5	18.5	Shale, fissile,	Olive Gray						
							1974		
					-3				
						ļ			
						Г	W1		
						,			
7 CONTR	ACTOR'S	OR LANDOWNER	S CERTIFICAT	1ON: This water well was	(1) constru	ucted. (2) rec	onstructed or (3) plu	aaed un	der my jurisdiction
				5/15/2009					knowledge and belief.
				527 This					
	business na			eoCore, Inc.		by (signat		Il	
				JULIU III.		7 (- 3			