County: Morris Fraction NW	SE NW Sec. 6 T /6 S R 6 PW
Owner: Hodgdon Powder Comp	WELL COMPLETION RECORD (WWC-5) ing or incorrect information)
Location was listed as:	Location changed to:
Section-Township-Range: 6-165-55	6-165-6E NW SE NW
Fraction (1/4 1/4 1/4): NW SE NW	NW SE NW
Other changes: Initial statements:	
Changed to:	
Comments:	
Verification method: Written & legal de area road map, and ma	pring tool on KG5 website. initials: DRAdate: 12/14/16 intrary 1930 Constant Ave. Lawrence KS 660473726
Submitted by: Kansas Geological Survey, Data Resources L	initials: DR 4 date: 12/14/16
to: Kansas Dept of Health & Environment, Bureau of Water	iorary, 1930 Constant 11vo., Davience, 110 000 173720

				TER WELL RECORD				
		ATER WELL:		/ OT //		ction Number		Range Number
	Morris	f			W 1/4	6	T 16 S	R 5 (E/)V
		on from nearest to Rd., Morris Co		et address of well if loc	ated within city	/?		
2 WATI	ER WELL C	WNER: Hodgd	on Powder C	ompany				
RR#, St.	Address, B	ox# : 2577 Q	Avenue				Board of Agriculture, Div	ision of Water Resources
City, Stat	e, ZIP Code	Hering	ton, Kansas	67449			Application Number:	
		LOCATION SECTION BOX:					ATION:	
_ ,		Ņ						3 ft.
! ↑							urface measured on mo/day	
	NW	NE					iter hours pu	
	X	!					fter hours pu	
lig M		↓F	1				and i	
-	ŀ		į .	R TO BE USED AS:			-	Injection well
	SW	SE	1 Domesti				9 Dewatering 12	· · · · · · · · · · · · · · · · · · ·
		1	2 Irrigation	n 4 Industrial	7 Lawn and g	arden only		
♥ L	!		submitted	avbacteriologicai şam	pie submitted t		YesNo ✓; If yes ter Well Disinfected? Yes	s, mo/day/yr samble was No ✓
L		<u>S</u>						
سے		CASING USED:		5 Wrought iron			CASING JOINTS: Glue	·
		3 RMP (SI	,	6 Asbestos-Cemen	t 9 Other	(specify belo	,	ded
(2) °		4 ABS		7 Fiberglass				aded. 🗸
1	-						ft., Dia	
Casing he	ight above	land surface	36	. in., weight			t. Wall thickness or gauge	No Sch 40
TYPE OF	SCREEN	OR PERFORATION	N MATERIAL		(7) PV		10 Asbestos-cen	nent
1 S	teel	3 Stainless	s steel	5 Fiberglass	8 RM	IP (SR)	11 Other (specify	()
2 B	rass	4 Galvaniz	ed steel	6 Concrete tile	9 AB	S	12 None used (o	pen hole)
SCREEN	OR PERFO	RATION OPENIN	IGS ARE:	5 Gau	zed wrapped		8 Saw cut	11 None (open hole)
1 0	ontinuous	slot (3)V	fill slot	6 Wire	wrapped		9 Drilled holes	İ
2 L	ouvered sh	utter 4 K	ey punched	7 Toro			10 Other (specify)	
SCREEN-	PERFORAT	ED INTERVALS:	From	$\dots 7 \dots \dots$ ft. to .	12	ft., Fro	om	to ft.
			From	ft. to .		ft., Fro	om	to ft.
	BRAVEL PA	CK INTERVALS:	From	6ft. to.	13.5	ft., Fro	om ft.	to ft.
			From	ft. to .		ft., Fro	om	to ft
6 GROU	MATERIA	L: 1 Neat	cement	2 Cement grout	3 Bento	nite 4	Other	
		m	. ft. to 2	ft., From	. 2 ft.	to 6	ft, From	
		ource of possible						Abandoned water well
1 Sep	tic tank	4 Later	ral lines	7 Pit privy			•	Dil well/Gas well
	er lines	5 Cess	s pool	8 Sewage lag	goon	12 Fertilizer storage 16 Other (specify below)		
	ertight sewe			9 Feedyard			ticido otorono	Other (specify below)
Direction 1	•	•	5 ,	•		How man	•	
FROM	TO		LITHOLOGIC	LOG	FROM	ТО	PLUGGING I	NTERVALS
0	0.5	Clay topsoil,	silty, Dark B	rown				
0.5	5	Clay, silty, Da						
5	6	Clay, very tig		wn				
6	8	Limestone, we						
8	12	Limestone, Yo					****	
12		Shale, fissile,						
12	10.0	CHAIC, HSSHE,	JHV GIAY					
						P	MW-7S, Abovegrade	
7 CONTR	ACTOR'S	R LANDOWNER	S CERTIFICAT	1ON: This water well v	vas (1) constru	cted, (2) reco	onstructed, or (3) plugged ur	nder my jurisdiction
				5/18/2009			cord is true to the best of m	
							completed øn (mo/day/yr)	6/17/2009
	ousiness na			eoCore, Inc.		by (signat	/ / A /// /	
							line or circle the correct answers.	
INICTOL	ICTIONS: Un-	typouritor or ball!	nt nan Die Are -					