

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Morris</u>	<u>SW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	<u>29</u>	T <u>16</u> S	R <u>7</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?
IN TOWN of Wilsey 710 Vorse

2 WATER WELL OWNER: <u>Betty Burnett</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>710 Vorse</u>	Application Number:
City, State, ZIP Code: <u>Wilsey KS 66873</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>70</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>60</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>32</u> ft. below land surface measured on mo/day/yr <u>Oct 22-03</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>10</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8</u> in. to <u>70</u> ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? <u>Yes</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>5</u> in. to <u>50</u> ft. Dia			11 Other (specify)
Casing height above land surface <u>14</u> in. weight			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	11 None (open hole)
SCREEN-PERFORATED INTERVALS:			
From <u>50</u> ft. to <u>70</u> ft.			
GRAVEL PACK INTERVALS:			
From <u>NONE</u> ft. to			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>3</u> ft. to <u>25</u> ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>West</u>			How many feet? <u>65'</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Top Soil BIK			
4	11	Clay TAN to Yel			
11	17	LIME Yel			
17	20	Shale TAN			
20	23	LIME TAN			
23	26	Shale Blue gray			
26	38	LIME Yel			
38	40	Shale Blue gray			
40	60	LIME Lize gray & Blue Flint			
60	61	Fracture			
61	70	LIME Gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>Oct 22-03</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>218</u> This Water Well Record was completed on (mo/day/yr) <u>Nov 17-03</u> under the business name of <u>ZINN Water Well Drlg</u> by (signature) <u>Joseph A. Zinn</u>
--