		L RECORD	Form W	WC-5		r Resources App. N		
		OF WATER WELL:	Fraction	1/	Section Number	Township No.	Range Number	
Coun	ty: Mo	cris ddress of Well Location;	1/4 SE 1/4 SE	1/4 SW 1/4	16	T 16 S	R7 KE W	
					Global Positioning			
	from nearest town or intersection: If at owner's address, check here 1 mile North & 1/2 mile East of Wilsey					Latitude: (in decimal degrees) Longitude: (in decimal degrees)		
1 1111	C NOL C	I & 1/2 HILLE DASC	Or wired	Elevation:				
2 WATER WELL OWNER: Jost Plumbing					Datum: WGS 84, NAD 83, NAD 27			
OODE TEMBERING				Collection Method: GPS unit (Make/Model:)				
C'ty Ctyle 700 Ctyle			ke, 1769 Hwy 56		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
	, ~	Hering	gton, KS 67449		Est. Accuracy: <	3 m, 3-5 m,	5-15 m, >15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 200 x 4 wells ft.								
		I AN "X" IN 4 DEPTH OF COMPLETED WELL						
SEC	N WELL'S STATIC WATER LEVEL. n/aft. below land surface measured on mo/day/yr11/1/12							
Г	Pump test data: Well water wasft. afterhours pumping							
EST. YIELD0							ping gpm	
w	Bore Hole Diameter 5in. to200. x. 4ft.					t., andft.		
	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SV	SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify belo							
	Irrigation Industrial Domestic-lawn & garden Monitoring well							
	Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted							
	1 mile Water well disinfected? \[Yes \] No							
5 TYPE OF CASING USED: Steel PVC X Other polyethyleneloops								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter 3/4 in. to 200 x 4t., Diameter in. to ft., Diameter ft.								
Casing height above land surface in., Weightlbs./ft., Wall thickness or gauge No								
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)								
☐ Steel ☐ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
From								
GRAVEL PACK INTERVALS: From								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From0 ft. to								
What is the nearest source of possible contamination:								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
Direction from well Distance from well Distan								
FROM 0	TO 2	Topsoil	JIC LUG	FROM	TO LITHO. L	OG (cont.) or PL	JOGING INTERVALS	
2	9	Clay, brown		+		N/200411-2-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-		
9	42	Limestone	a and a surface of the surface of th			WING WATER TO THE PARTY OF THE		
42	47	Shale, gray						
47	200	Shale, red/gray						
	-					4		
	-							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) 11/1/12 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on any day/year 11/20/12								
under the business name of Peterson Irrigation, Inc. by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212								