	ON OF WATER	R WELL:	Fraction	ے ب	4.5.7	Section Num	1 3	Number	Range I	$\overline{}$
	MORISIS				NW 1/4		T i €	? <u>S</u>	R 8	(E/)V
Distance a	ina direction tro	m nearest town o	or city street ad	aress of well i	r located within	City?				
			4.11.4 # 1							
		R: FRED	MILLER	-						_
	Address, Box #		LLEY S						Division of Wa	ter Resources
	, ZIP Code						Applica			
LOCATI	E WELL'S LOC	ATION WITH	DEPTH OF CO	MPLETED W	ELL	ft. ELI	EVATION:			
~ AN "X"	IN SECTION B	De	pth(s) Groundw	vater Encounte	red 1		ft. 2	ft. 3	3	
ī	!	ı Wı	ELL'S STATIC	WATER LEVE	L	. ft. below land	surface measured	l on mo/day/yr		
	NW I	NE	Pump	test data: W	ell water was		ft. after	hours pu	ımping	gpm
	\\\	Es	t. Yield	gpm: W	ell water was		ft. after	hours pu	ımping	gpm
<u>.</u> l	iyL	Bo	re Hole Diamet	ter	.in. to		ft., and	in	. to	.
₩ 	1	ı ˈwɪ	ELL WATER TO	D BE USED A	S: 5 Publi	c water supply	8 Air condition	ning 11	Injection well	
7	I I	1	1 Domestic	3 Feedlo	ot 6 Oil fi	eld water supply	9 Dewatering	12	Other (Specify	below)
	- 3W -	- 35	2 Irrigation	4 Industi	rial 7 Lawn	and garden on	ly 10 Monitoring	well		
1 1	i 1	l Wa	as a chemical/b	acteriological s	ample submitte	d to Department	? YesNo.	; If yes	, mo/day/yr sar	nple was sub
1 -	Ş	mi	tted				Water Well Disinfe	ected? Yes	No	
5 TYPE (OF BLANK CAS	SING USED:		5 Wrought iro	on 8	Concrete tile	CASING	JOINTS: Glue	d Clam	nped
1 Ste	eel	3 RMP (SR)		6 Asbestos-C	ement 9	Other/specif/ t	elow)	Weld	led <i>.</i>	
2 P\	/C	4 ABS		7 Fiberglass		NOCK		Thre	aded	
Blank casi	ing diameter	<i>40</i> in.	to	ft., Dia .		.in. to	ft., Dia		in. to	ft.
							lbs./ft. Wall thickne			
_	=	PERFORATION N				7 PVC		Asbestos-ceme		
1 Ste	eel	3 Stainless st	eel	5 Fiberglass		8 RMP (SR)	11	Other (specify))	
2 Br		4 Galvanized		6 Concrete til		9 ABS		None used (or		
		TION OPENINGS		:	5 Gauzed wrap	ped	8 Saw cut	` .	11 None (op	en hole)
1 Continuous slot 3 Mill slot				6 Wire wrapped			9 Drilled hol	es		,
	uvered shutter	4 Kev	punched		7 Torch cut		10 Other (sp	ecify)		
	PERFORATED	•			ft. to	ft.	From			
							From			
(GRAVEL PACK	INTERVALS:					From			
			From				From		to	
6 GROUT	T MATERIAL:	1 Neat cem	nent 2	2 Cement grou		2Bentonite				
Grout Inte	rvals: From.	.4.5ft.					ft., Fron	1 	ft. to	
What is th	ne nearest sour	ce of possible con	ntamination:			10 L	ivestock pens	14 A	bandoned wat	er well
1 Se	eptic tank	4 Lateral I	ines	7 Pit p	rivy	11 F	uel storage	15 C	Dil well/Gas we	41
2 Sewer lines 5 Cess pool		ol	8 Sewage lagoon		12 F	12 Fertilizer storage 16 Other (specify below			pelow)	
		lines 6 Seepage	e pit	9 Feed	dyard	13 li	nsecticide storage		CF WAT	
	from well?	, •	•		•		many feet?			
FROM	то		LITHOLOGIC L	-OG	FR	ОМ ТО		PLUGGING	INTERVALS	
0	4.5	T6PS616								
4.5	5.5	BENTO	NITE							
5.5	7	5UBSO	14							
7	15	SAND								
	†									
	 									
	tt									
	 									
	 									
	 									
	 									
	<u> </u>					L				
							reconstructed, or (
completed	l on (mo/day/ye	ar) 					record is true to the	1-10	nowledge and t	elief. Kansas
Water We	II Contractor's L	icense No		This V	Vater Well Rec	ord was comple	ted on (mo/day/yr)	44744	<i>[.]</i> ,	
under the	business name	of				by (s	ignature)	-cm	itto 1-	<u> 7-71</u>
INSTRU	JCTIONS: Use typev th and Environment	vriter or ball point pen. , Bureau of Water, Top	PLEASE PRESS Floreka, Kansas 66620	RMLY and PRINT of 10001. Telephone:	clearly. Please fill in 913-296-5545. Send	blanks, underline or d one to WATER WE	circle the correct answer	ers. Send top three one for your record	copies to Kansas s.	Department

WATER WELL RECORD Form WWC-5 KSA 82a-1212