

1 LOCATION OF WATER WELL: County: Morris NE 1/4 NW 1/4 NE 1/4 East 1/2 7 Township Number T 16 S Range Number R 9 EW

Distance and direction from nearest town or city street address of well if located within city? 3 mile West & 1 mile North of Council Grove - E45 Council Grove LAKE

2 WATER WELL OWNER: Gary Schmidt 1400 Pinnacle Drive Wichita, KS 67230

Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NE section]

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 38 ft. below land surface measured on mo/day/yr JAN 9 - 04

WELL'S STATIC WATER LEVEL: 32 ft. below land surface measured on mo/day/yr JAN 9 - 04

Pump test data: Well water was 4 gpm: Well water was 60 ft. after 3 hours pumping 12 gpm

Est. Yield 4 gpm: Well water was 60 ft. after 3 hours pumping 12 gpm

Bore Hole Diameter: 8 5/8 in. to 60 ft. and 12 in. to 60 ft.

WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: 2 Welded 3 Threaded

2 PVC 4 ABS 7 Fiberglass 9 Other (specify below)

Blank casing diameter 5 in. to 38 ft. Dia 18 in. weight 18 lbs./ft. Wall thickness or gauge No. SDR-20

Casing height above land surface 18 in.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 38 ft. to 60 ft. From 60 ft. to 60 ft.

GRAVEL PACK INTERVALS: From NO ft. to 60 ft. From 60 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 25 ft. From 25 ft. to 60 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) House

13 Insecticide storage

Direction from well? West How many feet? 55

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) JAN 9 - 04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 210 This Water Well Record was completed on (mo/day/yr) JAN 27 04 under the business name of Zinn Water Well Drllg by (signature) Joseph A. Zinn

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.