

1 LOCATION OF WATER WELL: County: Morris		Fraction NW ¼ SW ¼ SE ¼	Section Number 8	Township Number T 16 S	Range Number R 8 E W																																																												
Distance and direction from nearest town or city street address of well if located within city? <u>2½ West & 2 North of Council Grove</u>																																																																	
2 WATER WELL OWNER: Scott McGINN RR#, St. Address, Box # : 1010 Douglas Drive City, State, ZIP Code : Sedgwick, KS 67135 Board of Agriculture, Division of Water Resources Application Number:																																																																	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;">N - - NW - - NE - - W E - - SW - - SE - - S</div>		4 DEPTH OF COMPLETED WELL 101 ft. ELEVATION: Depth(s) Groundwater Encountered 1 40 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr MAY 22 06 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 1 Pint gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yrs sample was submitted Water Well Disinfected Yes No																																																															
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 32 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 16 in., weight lbs./ft. Wall thickness or gauge No. SDR-26 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 32 ft. to 101 ft., From ft. to ft. GRAVEL PACK INTERVALS: From NONE ft. to ft., From ft. to ft.																																																																	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 24 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Lateral Field Direction from well? West How many feet? 100																																																																	
<table border="1" style="width:100%; border-collapse: collapse;"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>8</td><td>LIME Lite</td><td></td><td></td><td></td></tr><tr><td>8</td><td>31</td><td>Shale Red-Green</td><td></td><td></td><td></td></tr><tr><td>31</td><td>46</td><td>LIME Gray Top: Fractured</td><td></td><td></td><td></td></tr><tr><td>46</td><td>63</td><td>Shale Gray</td><td></td><td></td><td></td></tr><tr><td>63</td><td>67</td><td>LIME Gray</td><td></td><td></td><td></td></tr><tr><td>67</td><td>71</td><td>Shale Gray Hd.</td><td></td><td></td><td></td></tr><tr><td>71</td><td>90</td><td>LIME & Flint</td><td></td><td></td><td></td></tr><tr><td>90</td><td>100</td><td>Shale Gray</td><td></td><td></td><td></td></tr><tr><td>100</td><td>101</td><td>LIME</td><td></td><td></td><td></td></tr></tbody></table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	8	LIME Lite				8	31	Shale Red-Green				31	46	LIME Gray Top: Fractured				46	63	Shale Gray				63	67	LIME Gray				67	71	Shale Gray Hd.				71	90	LIME & Flint				90	100	Shale Gray				100	101	LIME			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																												
0	8	LIME Lite																																																															
8	31	Shale Red-Green																																																															
31	46	LIME Gray Top: Fractured																																																															
46	63	Shale Gray																																																															
63	67	LIME Gray																																																															
67	71	Shale Gray Hd.																																																															
71	90	LIME & Flint																																																															
90	100	Shale Gray																																																															
100	101	LIME																																																															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) MAY 22 06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 210 This Water Well Record was completed on (mo/day/yr) JUN 8 06 under the business name of ZINN Water Well Only by (signature) Joseph A. Zinn																																																																	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.																																																																	