

1 LOCATION OF WATER WELL: Fraction CW W2 1/4 NW 1/4 Section Number 8 Township Number T 16 S Range Number R 80 EW
County: MORRIS
Distance and direction from nearest town or city street address of well if located within city? About 3 miles to dam then South across

2 WATER WELL OWNER: GENE L. BEEM
RR#, St. Address, Box #: 1417 LE GORELANE
City, State, ZIP Code: MANHATTAN KS 66502
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
N
W E
S
1 Mile
4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION:
Depth(s) Groundwater Encountered 1.75 x 1.25-30 ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter: 8 in. to ft., and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes No ✓; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes ✓ No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) Welded
② PVC 4 ABS Threaded
Blank casing diameter 5 in. to 60 ft. Dia. 5 in. to 80 ft. Dia. 120 in. to ft.
Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No. 160
TYPE OF SCREEN OR PERFORATION MATERIAL: ⑦ PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped ⑧ Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft. From 120 ft. to 140 ft.
GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: ① Neat cement ② Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 12 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
① Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? WEST How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	DIRT & GRAVEL			
2	23	ROCK YELLOW			
23	30	SHALE BLUE			
30	45	SHALE RED			
45	55	SHALE BLUE			
55	60	LIME GRAY			
60	80	SHALE BLUE			
80	87	SHALE RED			
87	90	LIME GRAY			
90	115	SHALE BLUE			
115	130	LIME WHITE			
130	140	SHALE BLUE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) APRIL 29, 1987 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 156 This Water Well Record was completed on (mo/day/yr) MAY 16, 1987
under the business name of L.H. KRAUSE SHOP by (signature) L.H. Krause
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.