

1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 SW 1/4 Section Number 13 Township Number T 16 S Range Number R 8 EAW

County: MORRIS Distance and direction from nearest town or city street address of well if located within city?

303-504th Council Grove

2 WATER WELL OWNER: Pat Brannon

RR#, St. Address, Box #: 303504th Council Grove 66846

Board of Agriculture, Division of Water Resources

City, State, ZIP Code

Application Number: NA

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 47 ft. ELEVATION: 21-28 ft.

Depth(s) Groundwater Encountered 1. 21 ft. 2. 28 ft. 3. 9-21-83 ft.

WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr 9-21-83

Pump test data: Well water was 20 gpm: Well water was 21 ft. after 8 hours pumping 47 gpm

Est. Yield 20 gpm: Well water was 21 ft. after 8 hours pumping 47 gpm

Bore Hole Diameter 10 in. to 21 ft., and 8 in. to 47 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued X Clamped X

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded X

2 PVC

4 ABS

7 Fiberglass

Threaded X

Blank casing diameter 6 in. to 21 ft., Dia 21 in. to 47 ft., Dia 160 in. to 47 ft.

Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. 160

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

SCREEN-PERFORATED INTERVALS:

From 21 ft. to 47 ft., From 21 ft. to 47 ft.

From 21 ft. to 47 ft., From 21 ft. to 47 ft.

GRAVEL PACK INTERVALS: From 12 ft. to 47 ft., From 12 ft. to 47 ft.

From 12 ft. to 47 ft., From 12 ft. to 47 ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 2 ft. to 12 ft., From 2 ft. to 12 ft., From 2 ft. to 12 ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

West 40'

How many feet? 40'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	1	TS BIK			
1	21	Cl Brn			
21	28	Gravel			
28	32	Sh Gray			
32	36	LS Gray Dense			
36	47	Sh Gray med Dense			
		TD47			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-21-83 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 203 This Water Well Record was completed on (mo/day/yr) 9-25-83

under the business name of McNee Drilling & Metals by (signature) J.C. McNee

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.