

mw-1

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Morris	NE 1/4 SW 1/4 NW 1/4	13	T 16 S	R 8 E

Distance and direction from nearest town or city street address of well if located within city?

611 E. Main, Council Grove, Kansas

2 WATER WELL OWNER:	City of Council Grove, 313 W. Main, Council Grove, KS			
RR#, St. Address, Box #:	Williams Fertilizer Attn: Rick Williams			
City, State, ZIP Code:	Rt. 1, Box 81, Council Grove, KS			
	Board of Agriculture, Division of Water Resources			
	Application Number: -----			

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 21.75 ft. ELEVATION: -----
	Depth(s) Groundwater Encountered 1. 16.8 ft. 2. ----- ft. 3. ----- ft.
	WELL'S STATIC WATER LEVEL 11.05 ft. below land surface measured on mo/day/yr 3/2/95
	Pump test data: Well water was ----- ft. after ----- hours pumping ----- gpm
	Est. Yield ----- gpm: Well water was ----- ft. after ----- hours pumping ----- gpm
	Bore Hole Diameter 8.625 in. to 21.75 ft., and ----- in. to ----- ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well mw-1	
Was a chemical/bacteriological sample submitted to Department? Yes ----- No -----; If yes, mo/day/yr sample was submitted -----	
Water Well Disinfected? Yes ----- No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ----- Clamped -----
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded X
Blank casing diameter ----- in. to 11.75 ft., Dia. SCH 40 PVC			Threaded -----
Casing height above land surface 0 in., weight ----- lbs./ft. Wall thickness or gauge No. -----			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From ----- ft. to 21.75 ft., From ----- ft. to ----- ft.			
GRAVEL PACK INTERVALS: From 10.0 ft. to 21.75 ft., From ----- ft. to ----- ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other -----
Grout Intervals: From 0 ft. to 8 ft., From 8 ft. to 10 ft., From ----- ft. to ----- ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Contaminated site
Direction from well? How many feet? -----				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL	3.25	Fill			Flush Mount Wai
3.25	17.00	Silty Clay			Don Taylor
17.00	21.00	Clayey Silt			2/15/95
21.00	21.75	Shale			
21.75	TD	END OF BOREHOLE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/2/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 3/23/95 under the business name of Associated Environmental, Inc. by (signature) D. Johnson for Daimin Duncan

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4