

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: MORRIS	SE 1/4 SW 1/4 NW 1/4	32	T 16 S	R 9 E

Distance and direction from nearest town or city street address of well if located within city?

3 1/2 M SE CO. BLACKTOP 1/2 SOUTH 1/2 E - COUNCIL GROVE

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #:	Application Number:
City, State, ZIP Code:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 37 ft. ELEVATION: -
	Depth(s) Groundwater Encountered 1. 25 ft. 2. - ft. 3. - ft.
	WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 10-05-89
	Pump test data: Well water was 20 ft. after 2 hours pumping 12 gpm
	Est. Yield 40 gpm: Well water was 3 ft. after - hours pumping - gpm
	Bore Hole Diameter 12.5 in. to 33 ft., and 8 1/2 in. to 37 ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department? Yes - No - ; If yes, mo/day/yr sample was submitted IS TO BE TESTED BEFORE DRINKING Well Disinfected? Yes - No -	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued - Clamped -
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 6 in. to 37 ft. Dia. - in. to - ft. Dia. - in. to - ft.			11 Other (specify) -
Casing height above land surface 62 in. weight 140 lbs./ft. Wall thickness or gauge No. -			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From 25 ft. to 37 ft. From - ft. to - ft. From - ft. to - ft. From - ft. to - ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 37 ft. From - ft. to - ft. From - ft. to - ft. From - ft. to - ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other -
Grout Intervals: From 3 ft. to 19 ft. From - ft. to - ft. From - ft. to - ft. From - ft. to - ft.				
What is the nearest source of possible contamination:				
* 1 Sepsic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well * 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)				
Direction from well? W - NW - E How many feet? 250 - 220 - 195 - 185				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	DK GRAY SILT			
3	25	CLAY SILT - CLAY CONTENT INCREASED - AS DEPTH INCREASED			
25	26	COURSE SILT + GRAVEL PARTICLES - WATER FLOWING FROM SOUTH TO NORTH			
26	33	LARGE + SMALL GRAVEL MIXED WITH LIME STONE RUBBLE - 6'-10' PLAT			
33	35	DK - GRAY SHALE			
35	37	OFF WHITE SHALE			
37	TD	LIME STONE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-05-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 10-05-89 under the business name of EBBERTS DRILLING by (signature) James Elbert
--