


1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number																																																																																																							
County: FRANKLIN		NW 1/4 SW 1/4 SE 1/4		24		T 17 S		R 17 EW																																																																																																							
Distance and direction from nearest town or city street address of well if located within city? 5 north, 3/8 west of Williamsburg																																																																																																															
2 WATER WELL OWNER: Thayne Bush																																																																																																															
RR#, St. Address, Box # : 215 N. Dane					Board of Agriculture, Division of Water Resources																																																																																																										
City, State, ZIP Code : Williamsburg, KS 66095					Application Number:																																																																																																										
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 240' ft. ELEVATION:																																																																																																												
<div style="text-align: center;">N 1 Mile W E S</div> 			Depth(s) Groundwater Encountered 1. 120-180' ft. 2. ft. 3. ft.																																																																																																												
			WELL'S STATIC WATER LEVEL 120' ft. below land surface measured on mo/day/yr 4-19-96																																																																																																												
			Pump test data: Well water was ft. after hours pumping gpm																																																																																																												
			Est. Yield 4 gpm: Well water was ft. after hours pumping gpm																																																																																																												
			Bore Hole Diameter 8. 3/4 in. to ft. and in. to ft.																																																																																																												
WELL WATER TO BE USED AS:																																																																																																															
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well																																																																																																															
2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)																																																																																																															
7 Lawn and garden only 10 Monitoring well																																																																																																															
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted																																																																																																															
Water Well Disinfected? Yes X No																																																																																																															
5 TYPE OF BLANK CASING USED:																																																																																																															
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped																																																																																																															
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded																																																																																																															
7 Fiberglass Threaded																																																																																																															
Blank casing diameter 5 in. to 0-120 ft. Dia 5 in. to 180-240 ft. Dia in. to ft.																																																																																																															
Casing height above land surface 24 in. weight 2.82 lbs./ft. Wall thickness or gauge No. 258																																																																																																															
TYPE OF SCREEN OR PERFORATION MATERIAL:																																																																																																															
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement																																																																																																															
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)																																																																																																															
12 None used (open hole)																																																																																																															
SCREEN OR PERFORATION OPENINGS ARE:																																																																																																															
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)																																																																																																															
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes																																																																																																															
7 Torch cut 10 Other (specify)																																																																																																															
SCREEN-PERFORATED INTERVALS: From 120 ft. to 180 ft. From ft. to ft.																																																																																																															
From ft. to ft. From ft. to ft.																																																																																																															
GRAVEL PACK INTERVALS: From 24 ft. to 240 ft. From ft. to ft.																																																																																																															
From ft. to ft. From ft. to ft.																																																																																																															
6 GROUT MATERIAL:																																																																																																															
1 Neat cement 2 Cement grout 3 Bentonite 4 Other																																																																																																															
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.																																																																																																															
What is the nearest source of possible contamination:																																																																																																															
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well																																																																																																															
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well																																																																																																															
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)																																																																																																															
13 Insecticide storage																																																																																																															
Direction from well? north How many feet? 200'																																																																																																															
<table border="1" style="width:100%; border-collapse: collapse;"><thead><tr><th colspan="3">LITHOLOGIC LOG</th><th colspan="3">PLUGGING INTERVALS</th></tr><tr><th>FROM</th><th>TO</th><th></th><th>FROM</th><th>TO</th><th></th></tr></thead><tbody><tr><td>0</td><td>3</td><td>Limestone-Loose</td><td>96</td><td>107</td><td>Shale-Grey</td></tr><tr><td>3</td><td>7</td><td>Shale-Yellow</td><td>107</td><td>108</td><td>Limestone-Grey</td></tr><tr><td>7</td><td>9</td><td>Shale-Black</td><td>108</td><td>110</td><td>Shale-Grey</td></tr><tr><td>9</td><td>12</td><td>Limestone-Grey</td><td>110</td><td>113</td><td>Sandstone-Grey</td></tr><tr><td>12</td><td>20</td><td>Shale-Grey</td><td>113</td><td>125</td><td>Shale-Grey</td></tr><tr><td>20</td><td>55</td><td>Limestone-Grey</td><td>125</td><td>153</td><td>Sandstone-Grey</td></tr><tr><td>55</td><td>67</td><td>Shale-Grey</td><td>153</td><td>161</td><td>Shale-Grey</td></tr><tr><td>67</td><td>70</td><td>Limestone-Grey</td><td>161</td><td>175</td><td>Sandstone-Grey</td></tr><tr><td>70</td><td>73</td><td>Shale-Grey</td><td>175</td><td>184</td><td>Shaley LS-Grey</td></tr><tr><td>73</td><td>74</td><td>Sandstone-Grey</td><td>184</td><td>190</td><td>Sandstone-Grey</td></tr><tr><td>74</td><td>75</td><td>Limestone-Grey</td><td>190</td><td>192</td><td>Shale-Grey</td></tr><tr><td>75</td><td>83</td><td>Shale-Grey</td><td>192</td><td>2 40</td><td>Sandy Shale-Grey</td></tr><tr><td>83</td><td>92</td><td>Limestone-Grey</td><td></td><td></td><td></td></tr><tr><td>92</td><td>94</td><td>Shale-Grey</td><td></td><td></td><td></td></tr><tr><td>94</td><td>96</td><td>Shale-Black</td><td></td><td></td><td></td></tr></tbody></table>										LITHOLOGIC LOG			PLUGGING INTERVALS			FROM	TO		FROM	TO		0	3	Limestone-Loose	96	107	Shale-Grey	3	7	Shale-Yellow	107	108	Limestone-Grey	7	9	Shale-Black	108	110	Shale-Grey	9	12	Limestone-Grey	110	113	Sandstone-Grey	12	20	Shale-Grey	113	125	Shale-Grey	20	55	Limestone-Grey	125	153	Sandstone-Grey	55	67	Shale-Grey	153	161	Shale-Grey	67	70	Limestone-Grey	161	175	Sandstone-Grey	70	73	Shale-Grey	175	184	Shaley LS-Grey	73	74	Sandstone-Grey	184	190	Sandstone-Grey	74	75	Limestone-Grey	190	192	Shale-Grey	75	83	Shale-Grey	192	2 40	Sandy Shale-Grey	83	92	Limestone-Grey				92	94	Shale-Grey				94	96	Shale-Black			
LITHOLOGIC LOG			PLUGGING INTERVALS																																																																																																												
FROM	TO		FROM	TO																																																																																																											
0	3	Limestone-Loose	96	107	Shale-Grey																																																																																																										
3	7	Shale-Yellow	107	108	Limestone-Grey																																																																																																										
7	9	Shale-Black	108	110	Shale-Grey																																																																																																										
9	12	Limestone-Grey	110	113	Sandstone-Grey																																																																																																										
12	20	Shale-Grey	113	125	Shale-Grey																																																																																																										
20	55	Limestone-Grey	125	153	Sandstone-Grey																																																																																																										
55	67	Shale-Grey	153	161	Shale-Grey																																																																																																										
67	70	Limestone-Grey	161	175	Sandstone-Grey																																																																																																										
70	73	Shale-Grey	175	184	Shaley LS-Grey																																																																																																										
73	74	Sandstone-Grey	184	190	Sandstone-Grey																																																																																																										
74	75	Limestone-Grey	190	192	Shale-Grey																																																																																																										
75	83	Shale-Grey	192	2 40	Sandy Shale-Grey																																																																																																										
83	92	Limestone-Grey																																																																																																													
92	94	Shale-Grey																																																																																																													
94	96	Shale-Black																																																																																																													
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-18-96 and this record is true to the best of my knowledge and belief. Kansas																																																																																																															
Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 5-6-96																																																																																																															
under the business name of STRADER DRILLING CO., INC. by (signature) Dale Adkerson																																																																																																															
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																																																															