


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 20 Township Number T 17 S Range Number R 17 EW
 County: Osage
 Distance and direction from nearest town or city street address of well if located within city?
1 mile South + 1.1 West of Quenemo, Ks.

2 WATER WELL OWNER: David Coffman
 RR#, St. Address, Box #: 900 Hwy 68 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Pomona, KS 66076 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 220 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 137-228 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 10.1 ft. below land surface measured on mo/day/yr 12-10-96
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 16 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 8 3/4 in. to 20 ft., and 7 7/8 in. to 20 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 210 ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface 30 in., weight 200 PSI lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 210 ft. to 220 ft. From ft. to ft.
 From ft. to ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 220 ft. to 20 ft. From ft. to ft.
 From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other
 Grout Intervals: From 20 ft. to 0 ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? SW How many feet? 75

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS Cont.
0	3	So. 1 + Clay	192	196	Shale
3	15	Limestone	196	198	Limestone
15	18	Clay	198	218	Sandstone
18	23	Shale	218	220	Shale
23	25	Limestone			
25	37	Shale			
37	42	Limestone			
42	48	Shale			
48	58	Limestone			
58	75	Shale			
75	78	Limestone			
78	93	Sand + shale			
93	95	Limestone			
95	137	Sand + shale			
137	192	Sandstone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 12-10-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 561 This Water Well Record was completed on (mo/day/yr) 12-10-96 under the business name of Evans Energy Dev. Inc. by (signature) Scott G.

OFFICE USE ONLY T R E W SEC. 1/4 1/4 1/4