WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| 1 1 2 5 1 | County | Fraction | | Section | number | Township number | Range number | |
|--|------------|-----------------|-----|-------------------------------------|---|--|---|--|
| 1. Location of well: | Franklin | sw 1/4 SW1/4 SW | 1/4 | 35 | | T 17 S | R 17 E/■ | |
| 2. Distance and direction from nearest town or city: 2w 3N 3. Owner of welMarry thayer R.R. or street: TRR | | | | | | | | |
| Street address of well location if in city: Williamberg | | | | y, state, zip codewilliamsberg kan. | | | | |
| 4. Locate with "X" in section below: | | | | | | 6. Bore hole dia. 64 in. Well depth 220 ft. | Completion date 3-24-78 | |
| 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | | | | | 7. X Cable tool Rotary Driven Dug | | |
| 4. Locate with "X" in section below: Control Contro | | | | | | Hollow rod Jetted Bored Reverse rotary | | |
| E X | | | | | | 8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock | | |
| COUNTRY ROAU | | | | | | Lawn Oi | il field water Other | |
| | | | | | | 9. Casing: Material Threaded Welded | - Height: Above or below Surface 2 4 in. Weight Scatto lbs./ft. | |
| S 1 Mile ———————————————————————————————————— | | | | | | PVC PVC Dia. Din. to 20 ft. dep | | |
| 5. Type and color of material | | | | From | То | Dia. Lin. to 220ft. dept | th gage No. Sch 40 | |
| | | | | | | 10. Screen: Manufacturer's n | LIME | |
| soil & clay | | | | 0 | 5 | Type PVC Slot/gauze | _ Dia | |
| lime | | | | 5 | 10 | Set between | ft, andft. | |
| | shald s | | | 10 | 14 | Gravel pack? A Size ra | nge of material | |
| lime | | | | 14 | 16 | 11. Static water level: | face Date 2-21-78 | |
| shald | | | | 16 | 3), | 12. Pumping level below land surfaces: | | |
| lime | | | | 3),183 | , | ft. after hrs. pumping g.p.m ft. after hrs. pumping g.p.m. | | |
| shald (black) | | | | 53 | 57 | Estimated maximum yield 13. Water sample submitted: | g.p.m. mo./day/yr. | |
| lime | | | | | | | Date | |
| | | | | 57 | 58 | 14. Well head completion: Pitless adapter 2 | inches above grade | |
| shald (light) | | | | 58 | 86 | 15. Well growted? | Bentonite Concrete | |
| lime | | | | 86_ | 10)ر | Depth: From B ft. to | 20 ft. | |
| shale | | | | 107 | 116 | 16. Nearest source of possible ft. Direction | e contamination: SCPTIC | |
| lime | | | | 116 | 121 | Well disinfected upon comple | etion?No | |
| grey sanded shald | | | | 127 | 180 | 17. Pump: Manufacturer's name | Not installed A CKET | |
| grey sand | | | | 180 | 215 | Model number 2011 Length of drop pipe 210 | | |
| grey shald | | | | | | Type:Submersible | Turbine | |
| | | | | 215 | 220 | Jet | Reciprocating Other | |
| (Use a second sheet if needed) 18. Elevation: 19. Remarks: | | | | | 1 | Centrifugal 20. Water well contractor's a | | |
| This Woll WAS Drilled | | | | | This well was drilled under m is true to the best of my know | | | |
| This Well WAS Drilled This Well WAS Drilled For old house | | | | | FDGAR SI | VANK 124 | | |
| stope | | | | | | Address Address | AWA KAN | |
| | | | | | | Signed Authorized rep | resentative Date 4-2-1 | |
| | | | | | | | | |