

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Franklin</u>	<u>SE 1/4 NW 1/4 SE 1/4</u>	<u>13</u>	<u>T 17 S</u>	<u>R 17E EW</u>

Distance and direction from nearest town or city street address of well if located within city?

3 South and 1 1/2 West of Pamona

2 WATER WELL OWNER:	<u>Bill Blake</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	<u>435 Kingman Rt.</u>	Application Number:
City, State, ZIP Code :	<u>Quenemo, Ks. 66528</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>200</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>134</u> ft. below land surface measured on <u>mo/day/yr 8-18-95</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>1.3</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>8 3/4</u> in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>5</u> in. to <u>140</u> ft. Dia			Threaded
Casing height above land surface <u>24</u> in., weight <u>2.82</u> lbs./ft. Wall thickness or gauge No. <u>258</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From <u>140</u> ft. to <u>200</u> ft.			
GRAVEL PACK INTERVALS: From <u>24</u> ft. to <u>200</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>4</u> ft. to <u>24</u> ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? <u>East</u>			How many feet? <u>110</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Brown clay	59	61	Grey limestone
2	4	Grey limestone loose	61	91	Grey shale 7 limestone
4	10	Yellow shale	91	106	Grey shale
10	13	Black shale	106	125	Grey shale sandy
13	15	Grey limestone	125	128	Grey sandstone
15	19	Grey shale	128	129	Grey shale
19	22	Grey limestone	129	175	Grey sandstone
22	24	Grey shale	175	178	Grey shale
24	26	Grey limestone	178	190	Grey sandstone
26	27	Grey shale	190	192	Grey limestone
27	37	Grey limestone	192	194	Greysandstone
37	47	Grey shale	194	197	Grey limestone
47	48	Black shale	197	200	Grey shale
48	53	Grey limestone			
53	59	Grey shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-18-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>182</u> This Water Well Record was completed on (mo/day/yr) <u>9-16-95</u> under the business name of <u>Strader Drilling Co., Inc.</u> by (signature) <u>Walter Skerren</u>
--