WATE	R WEI	LL RECORD	Form WWC	C- 5	Division of Wate	r Resources App. No	
1			ction		Section Number	Township No.	Range Number
			1/4 SW 1/4 SW 1/4		14		R 17
		Address of Well Location; if unl	Global Positioning System (GPS) information:				
from nearest town or intersection: If at owner's address, check here .					Latitude: .38.567194 (in decimal degrees)		
2514 Alabama Terrace					Longitude: 95.504806 (in decimal degrees) Elevation:		
Quenemo, KS 66528					Datum: WGS 84, NAD 83, NAD 27		
2 WATER WELL OWNER: William Miller					Collection Method:		
RR#, Street Address, Box #: 19307 W 98th St.					GPS unit (Make/Model:)		
City, State, ZIP Code : Lenexa, KS 66220-9725					Digital Map/Photo, Topographic Map, Land Survey		
Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m							
1	H AN "X	1	ft.				
SECTION BOX: Depth(s) Groundwater Encountered (1).230 ft. (2) ft. (3)							
SECTION BOX: Depth(s) Groundwater Encountered (1).230							
Pump test data: Well water wasft. after hours pumping							
EST. YIELD. ±/-10. gpm. Well water was							
W Bore Hole Diameter 10 in. to .270 ft., and							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Swap as Section Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
SE - Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes V No							
S If yes, mo/day/yr sample was submitted							
	I mile	Water well disinfecte	d? ☑ Yes ☐ No				
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded							
Casing diameter .10. in. to .270. ft., Diameter in. to ft., Diameter in. to ft.							
Casing height above land surface 18 in., Weight SCH 40 lbs./ft., Wall thickness or gauge No200 PSI							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
GRAVEL PACK INTERVALS: From 25 ft. to 270 ft., From ft. to ft.							
From							
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ✓ Bentonite ☐ Other							
Grout Intervals: From .0							
What is the nearest source of possible contamination:							
Septic tank							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well							
Direction from well							
FROM		LITHOLOGIC L		ROM			GGING INTERVALS
0	16	Clay					
16	65	Shale					
65	71	Limestone					
71	76	Sandstone					
76	80	Limestone					
80	121	Shale				0 J B A 2000 -	
121	171	Sandy Shale			Original Returned to Sender		
171 180	180 230	Limestone Shale				or Correction	n Date: <u> 0/20/</u> 10
230	270						7
230 270 Sandstone							
under my jurisdiction and was completed on (mo/day/year)							
Kansas Water Well Contractor's License No. 595 This Water Well Record was completed on (mo/day/vear) 10 113 11							
Kansas Water Well Contractor's License No. 595 This Water Well Record was completed on (mo/day/year) 10.131 under the business name of Jesse Yoaklem Well Dilling by (signature)							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PDNT</u> clearly. Please fill in blanks and check the orrect answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 120, Topeka, Kansas 66612-1367.							
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							

Check: White Copy, Blue Copy, Pink Copy