	LL RECORD	Form WV	VC-5	Division of Wate	r Resources App. N	0
1 LOCATION OF WATER WELL:			1, ,	Section Number	Township No.	Range Number
County: Franklin Street/Rural Address of Well Location; it		NW SE "SE	14 56 14			R I DE DW
			Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here .				Latitude: (in decimal degrees)		
261 Labette Road Pomona, Kansas			Longitude: (in decimal degrees)			
				Elevation:		
2 WATER WELL OWNER: Longie Harris				Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27		
Lorino Harrio			Collection Method:			
C'es Cests ZID Cests				☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
Topeka		, Kansas 66609		Est. Accuracy:		
3 LOCATE WELL						
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 220 ft.						
SECTION BO	OX: Depth(s) Groundwater Encountered (1) 158-204 ft (2) ft (3)					
N	WELL'S STATIC WATER LEVEL. 116ft. below land surface measured on mo/day/yr. 4/2/2013					
Pump test data: Well water wasft. after hours pumpinggpm						
FOT VIELD 12						
w NW N	E Bore Hole Diam	eter 8 3/4 in to 2	20 f	and in	to	fi Spin
W Bore Hole Diameter 8 3/4 in. to .220 ft., and in. to						
P Demostic P Ecodlet P Oil fold system symple P Described P Ott (Sec. 15, 1-1-)						
Was a chemical/bacteriological sample submitted to Department? Yes No						
s					103 110	
S If yes, mo/day/yr sample was submitted						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded						
Casing diameter .5						
Casing height above land surface. 30 in., Weight SDR21 lbs./ft., Wall thickness or gauge No200 PSI						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From						
From						
GRAVEL PACK INTERVALS: From. 220 ft. to .30 ft., From ft. to .ft.						
From						
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other						
Grout Intervals: From .30 ft. to .0 ft., From						
What is the nearest source of possible contamination: None of Drilling						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well						
Sewer lines						
Direction from well						
FROM TO	LITHOLOG		FROM			IGGING INTERVALS
0 7			INOM	LITIO. L	A (COIL) OF FLC	COULTO INTERVALS
7 12	soil & clay 194-195 co					·
	lime 195-204 sa					
12 23	shale 204-220 sh	iale				
23 26	lime					
26 27	shale					
27 33	lime					
33 158	shale					
158 186	sand					
186 188	shale					
188 194	sand					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged						
under my jurisdiction and was completed on (mo/day/year) .4/2/2013 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 56.1 This Water Well Record was completed on (mo/day/year)						
under the business name of Eyans Energy Development, Inc. by (signature)						
INSTRUCTIONS: Use ty pewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) t	o Kansas Depar tment of Health	and E nvironment, Bureau of	f Water, Geolo	gy Section, 1000 SW Jac	ckson St., Suite 420,	Topeka, Kansas 666 12-1367.
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at						
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						