


1 LOCATION OF WATER WELL: County: Franklin Fraction: SE 1/4 SE 1/4 SE 1/4 Section Number: 24 Township Number: T 17 S Range Number: R 18 E

Distance and direction from nearest town or city street address of well if located within city? 2N 1 1/2 E Homewood

2 WATER WELL OWNER: Tom Parlin RR#, St. Address, Box #: R.R. City, State, ZIP Code: 0 Kansas Kan. Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 

4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: 66 ft.

Depth(s) Groundwater Encountered: 55 ft. below land surface measured on mo/day/yr 7-30-85

WELL'S STATIC WATER LEVEL: 55 ft. below land surface measured on mo/day/yr 7-30-85

Pump test data: Well water was 3 gpm: Well water was 20 ft. after 9 hours pumping 20 gpm

Est. Yield: 3 gpm: Well water was 20 ft. after 9 hours pumping 20 gpm

Bore Hole Diameter: 9 in. to 20 ft., and 20 in. to 20 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
7 Fiberglass Threaded X

Blank casing diameter: 5 1/2 in. to 69 ft., Dia 5 in. to 89 ft., Dia 100 in. to 100 ft.

Casing height above land surface: 18 in., weight 52 lbs./ft. Wall thickness or gauge No. 52

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 69 ft. to 89 ft. From 89 ft. to 100 ft.

GRAVEL PACK INTERVALS: From 69 ft. to 89 ft. From 89 ft. to 100 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 21 ft. From 21 ft. to 100 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage

Direction from well? None at The Time How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	10	Soil & Clay			
10	50	Yellow Sand Rock			
50	65	Grey Shale			
65	75	Grey Sand			
75	89	White Sand			
89	100	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-30-1988 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 371 This Water Well Record was completed on (mo/day/yr) 7-30-1988 under the business name of Swank Drilling by (signature) Roger Swank

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

Prepaid J.E.D.