


1 LOCATION OF WATER WELL: County: FRANKLIN	Fraction NW 1/4 NW 1/4 SW 1/4	Section Number 25	Township Number T 17 S	Range Number R 18 EW
--	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1 1/2 MI. NORTH RITCHIE, KANS.

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code : RICHAUD ECORD ROMONA KAN. 66076	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 135 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 90 ft. 2. 90 ft. 3. 90 ft. WELL'S STATIC WATER LEVEL 90 ft. below land surface measured on mo/day/yr Pump test data: Well water was 10 gpm after 6 3/4 hours pumping Est. Yield 10 gpm Well water was 6 3/4 ft. after 6 3/4 hours pumping Bore Hole Diameter 6 3/4 in. to 6 3/4 in. and 6 3/4 in. to 6 3/4 in. WELL WATER TO BE USED AS: ☒ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Irrigation ☐ Industrial ☐ Lawn and garden only ☐ Observation well Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, mo/day/yr sample was submitted
--	---

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC Blank casing diameter 6 in. to 20 ft. Dia. 12 in. weight 12 lbs./ft. Wall thickness or gauge No. 5 CH 40 Casing height above land surface 12 in. weight 12 lbs./ft. Wall thickness or gauge No. 5 CH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From NONE ft. to NONE ft. From NONE ft. to NONE ft. From NONE ft. to NONE ft. GRAVEL PACK INTERVALS: From NONE ft. to NONE ft. From NONE ft. to NONE ft. From NONE ft. to NONE ft.	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued ☒ Clamped ☐ Welded ☐ Threaded ☐
---	--

6 GROUT MATERIAL: Grout Intervals: From 3 ft. to 20 ft. From 3 ft. to 20 ft. From 3 ft. to 20 ft. From 3 ft. to 20 ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Scape pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? South How many feet? 100	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
---	---

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	SOIL			
4	17	CLAY			
17	45	YELLOW SAND ROCK			
45	81	GREY SANDED SHALE			
81	100	GREY SAND			
100	135	WHITE SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-12-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 486 This Water Well Record was completed on (mo/day/yr) 1-18-88 under the business name of EDGAR SWANK DRILLING & PUMP REPAIR (signature) Edgar Swank

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.