WATE	R WEL	L RECORD	Form WV	VC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: Franklin		Fraction SE ¼ NW ¼ NE	1/4 1/4	Section Number Township No. Range Number	
Street/Rural Address of Well I ocation: if unknown distance & direction Clabal Positioning System (CPS) information:					
from nearest town or intersection: If at owner's address, check here . L					Latitude: N 38.34' 42.2" (in decimal degrees)
4 miles southwest of Ottawa					Longitude: W 95 24' 10.5" (in decimal degrees) Elevation:
					Datum: WGS 84, NAD 83, NAD 27
		ELLOWNER: Eric Gue	enther		Collection Method:
1	,		bette Road		GPS unit (Make/Model: Hand Held Unit
City	, State, Z	IP Code : Ottawa.	KS 66067		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
3 LOCATE WELL					
1	H AN "X'		COMPLETED WELL		
SEC	TION BO N	X: Depth(s) Ground WELL'S STATI	lwater Encountered (C WATER LEVEL30	1).8Uft.	ft. (2) ft. (3) ft. below land surface measured on mo/day/yr
		Pump	test data: Well water	was	ft. after hours pumping gpm
EST. YIELD. 15					ft. after hours pumping gpm
W E Bore Hole Diamete			eterin. to	f	t., andft.
			TO BE USED AS:	Public water	er supply Geothermal Injection well
SV	V S	✓ Domestic	☐ Feedlot ☐ O	il field wate	r supply
SW SE Domestic Feediot On field water supply Dewatering Other (specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well					
ļ <u>—</u>		Was a chemical/	bacteriological sample s	submitted to	Department? Yes No
	S		day/yr sample was subn		
1 mile Water well disinfected? ✓ Yes □ No					
5 TYP	E OF CA	SING USED: Steel	V PVC □ Ot	ther	
CASIN	G JOINT	'S: 🗹 Glued 🔲 Clan			
Casing diameter .6 in. to .80 ft., Diameter .6 in. to .110 ft., Diameter in. to ft.					
Casing height above land surface. 24 in., Weight 200 PSI lbs./ft., Wall thickness or gauge No. SCH 40					
		EN OR PERFORATION			<i>gg.</i>
	Steel	Stainless Steel	V PVC		Other (Specify)
	Brass	Galvanized Steel	None used (open hol	le)	(-1
SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From80					
From					
GRAVEL PACK INTERVALS: From					
From					
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other					
Grout Ir		From ft. to	ft., From .	1	t. to ft., From ft. toft.
		st source of possible conta		1	
	Septic tar			Livestock p	
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well					
Direc	ction fron	ıı SW			rom well 200'.
FROM	ТО	LITHOLOG		FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0	37	Silty Clay			
37	73	Shale			
73	80	Limestone			
80	91	Sandstone			
91	110	Shale			
31		Ondie			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) 4.7/2.4 and this record is true to the best-of my knowledge and belief.					
Kansas Water Well Contractor's License No. 59.5 This Water Well Record was completed on (mo/day/wear) 12/31/07					
under the business name of Jesse Yoak winkfell Dvilling by (signature) level 1					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blacks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of 55.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html .					
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					
winte Copy, \square Blue Copy, \square Pink Copy					