WATER WELL REC	ORD	Form W	WC-5	Division of Wat	er Resources App. No).	
1 LOCATION OF WAT	ER WELL: F	raction	and the second s	Section Number	Township No.	Range Number	
County: Frankle			1/4 NG 1/4	27	T 17 S	R 18 NE DW	
Street/Rural Address of				Latitude: 38	g System (GPS) in 2 38. 7)	formation: (in decimal degrees)	
from nearest town or intersection: If at owner's address, check here .				Latitude: .38.33.38.77 (in decimal degrees) Longitude: N. 15.23.50.29 (in decimal degrees)			
				Elevation:! 0.	89		
2 WATER WELL OWNER: SANHELLIS				C-11 1 1 - 1 - 1 - 1 - 1	84, □ NAD 83, □		
RR#, Street Address, Box #: 22110 Georgia Rd.				☐ GPS unit (Make/Model: Congla Earth) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
2 WATER WELL OWNER: Scott Ellis RR#, Street Address, Box #: 2216 Georgia Rd. City, State, ZIP Code: Ottowa, Ks.				Digital Map/Photo, Topographic Map, Land Survey Est. Accuracy: <a> <a><a> <a><a><a><a><a><a><a><a><a><a><a><a>			
3 LOCATE WELL -			_			J-13 III, / 13 III	
		MPLETED WELI				a) a	
SECTION BOX:	Depth(s) Groundwater Encountered (1). 8.1						
errania estro manda pada de la compania de la comp	Pump test data: Well water wasft. after						
NIW NIE EST. YIELD. 2gpm., Well water was							
W E Bore Hole Diameter S						II.	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify belget)							
Irrigation Industrial Domestic-lawn & garden Monitoring well REPUBLISHENT							
was a chemical bacteriological sample submitted to Department:						' Wells	
S If yes, mo/day/yr sample was submitted							
water went distincted: [2] Tes [1] No							
5 TYPE OF CASING USED: Steel > PVC Other CASING IOINTS: Steel Clamped Welded Threaded							
CASING JOINTS: A Glued Clamped Welded Threaded Casing diameter 5.50 in. to 80 in. ft., Diameter 5.50 in. to 60 in. t							
Casing height above land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
Steel Stainless Steel TYC Other (Specify)							
SCREEN OR PERFORAȚION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 300							
From 13.0 ft to 3.0 ft From ft to ft							
GRAVEL PACK INTERVALS: From 200 ft. to 23. ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
What is the nearest source of possible contamination:							
Septic tank							
Watertight sewer lines Seepage pit Feedyard Fertilizer st				orage 🔲 Oil well/g	gas well		
Direction from well) outro we sa	<u>)</u>	T	from well 15 <i>D</i> .			
FROM TO	LITHOLOGIC		FROM	TO LITHO. I	LOG (cont.) <u>or</u> PLU	IGGING INTERVALS	
D I BLACK	2 organil n	ensoll retuel sin	and ma				
		wohale	U(MO)U				
	use Shalle		to real.	hard			
	parastone	W/ Gray shy	ele otros				
		ne simest					
		and Elimenz	one				
162 200 Gray	WK KKKK						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, or plugged							
under my jurisdiction and was completed on (mo/day/year) *1/2**							
under the business name of GERNUMMENTAL DILLIA. by (signature James Buku)							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT-clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
(white, blue, pink) to Kansas De Telephone 785-296-5524. Send							
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212							